

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

5. Lease Designation and Serial No.

SF-079938

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Jones LS #4

9. API Well No.

3004521191

10. Field and Pool, or Exploratory Area

Blanco Pictured Cliffs

11. County or Parish, State

San Juan New Mexico

1. Type of Well
☐ Oil Well ☒ Gas V. Well ☐ Other

2. Name of Operator

Amoco Production Company

Attention:

Gail M. Jefferson, Rm 1295C

3. Address and Telephone No.

P.O. Box 800, Denver, Colorado 80201

(303) 830-6157

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1460' FNL 1180' FEL

Sec. 35 T 29N R 8W

Unit H

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

MIRUSJ 3/6/96. RU HES, TIH set CIBP at 2810'. Test casing from 2810' to surface for 15 minutes to 500#. Held okay. Spot 15 sxs Class B cement on top of CIBP from 2810' to 2210'.

Perforated at 2050' w/2 jspf, .340 inch diameter, total 2 shots fired. Pressure tested perfs to 500#, could not pump into perfs, will spot cmt plugs across perfs. Perforated at 1900' w/2jspf, .340 inch diameter, total 2 shots fired. Pressure tested perfs to 500#, could not pump into perfs will spot a cmt plug across perfs.

Spot cement across perfs at 2050' and 1900' with 25 sxs Class B from 2100' to 1192', inside casing, could not pump into perfs.

Perforated at 607' w/2jspf, .340 inch diameter, total 2 shots fired. Pumped 150 sxs Class B cmt down casing at 607' out perfs and circ to surface out BH valve, circulated good cmt.

Cut off wellhead and install P&A marker.

RDMOSU 3/7/96.

14. I hereby certify that the foregoing is true and correct

Signed

Gail M. Jefferson

Title

Sr. Admin. Staff Asst.

Date

3/22/96

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

APPROVED

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

NMOC

DISTRICT MANAGER

* See Instructions on Reverse Side