Form 3160-5 (November 1983) (Formerly 9-331)

16.

## UNITED STATES DEPARTMENT OF THE INTERIOR (Other Interior Verse side)

BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE. instructions on re-

Form approved. Budget Bureau No. 1004-0135 Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO. NM 0560422

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

San Juan

t.

SUNDRY	NOTICES	AND	REPORTS	ON	WELLS
--------	---------	-----	---------	----	-------

(Do not use this form for prop Use "APPLIC	onais to drill or to deepen or p CATION FOR PERMIT—" for s	plug back to a different reservoir such propossis.)	·.	
OIL GAS THEE		RECEIVE	7. UNIT AGREEME	AMEN TH
2. NAME OF OPERATOR El Paso Natu	ral Gas Company	AUG 28 1985	8. FARM OR LEAS El Paso	
3. ADDRESS OF OPERATOR PO Box 4289,	Farmington, NM	BUREAU OF LAND MANAGEME	9. WELL NO.	
4. LOCATION OF WELL (Report location	clearly and in accordance with 2210'N, 620'W	EARMINGTON RESOURCE ARE		ic.Cliffs Ex
			11. SEC. T. R., M. SURVEY OR Sec. 20,	
14. PERMIT NO.	15. ELEVATIONS (Show wheth	ber DF, RT, GR, etc.)	12. COUNTY OR P	141111
	5671	5 1 C I	San Jua	n NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

5635 'GL

NOT	ICE OF	INTENTION TO:			BUB	BEQUI	INT REPORT OF:
		PULL OR ALTER CASING		7			BEPAIRING WELL X
TEST WATER SHUT-OFF	j	PULL OR ALTER CASING		-	WATER SHUT-OFF		REPAIRING WELL
FRACTURE TREAT		MULTIPLE COMPLETE		.]	FRACTURE TREATMENT	_	ALTERING CASING
SHOOT OR ACIDIZE		ABANDON*			SHOOTING OR ACIDIZING		ABANDONMENT*
REPAIR WELL		CHANGE PLANS			(Other)		
(Other)							of multiple completion on Well

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

Pull 1 1/4" tbg and packer. Move on location and rig up. 8-6-85 Spotted sand plug.

Isolated casing failure from 513'-771'. Squeeze cemented 8-7-85 with 175 sks. Class "B" with 2% calcium chloride and 1% TIC (190 cu.ft.). WOC 12 hrs.

Drilled out cement. Pressure tested casing, did not hold. 8-8-85 Isolated leak between 578-643'. Squeeze cemented with 75 sks. Class "B" with 2% calcium chloride and 1% TIC. cu.ft.) WOC:12 hrs.

Drilled out cement. Pressure tested casing to 600 psi, ok. 8-9-85

Cleaned out to 2154' with N2. Ran 65 jts. 1 1/4", 2.33#, 8-10-85 J-55 tubing, set at 2094'. Baker packer set @ Loaded tubing-casing annulus with corrosion inhibitor.

SIGNED SIGNED Leggy Sand	TITLE	Drilling Clerk	B-27-85
(This space for Federal or State office use)	TITLE	NECE! VE	EPTED FOR RECORD
CONDITIONS OF APPROVAL, IF ANY:	14140	AUG 3 0 1985	AUG 2 9 1985
· *(	See Instructio	ns on Reverge Ride DIVAY	Smm