

*CORRECTED COPY

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved
Budget Bureau No. 42 R1424.
5. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR EL PASO NATURAL GAS COMPANY		8. FARM OR LEASE NAME Grambling
3. ADDRESS OF OPERATOR BOX 990, FARMINGTON, NEW MEXICO 87401		9. WELL NO. 3A
4. LOCATION OF WELL. (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1600' N, 800' W		10. FIELD AND POOL, OR WILDCAT Blanco Mesa Verde
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 22, T-29-N, R-9-W N.M.P.M.
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 5729' GL		12. COUNTY OR PARISH San Juan
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*


(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-28-76 T. D. 2418'. Ran 60 joints 7", 20#, KS intermediate casing, 2406' set at 2418'. Cemented with 298 cu. ft. cement. W.O.C. 12 hours, held 1200#/30 minutes.

10-1-76 T. D. 4848'. Ran 82 joints 4 1/2", 10.5#, KS casing liner, 2598' set 2250-4848'. Float collar set at 4831'. Cemented with 450 cu. ft. cement. W.O.C. 18 hrs.

10-26-76 P.B.T.D. 4831'. Tested casing to 3500#, O.K. Perfed 3775, 3851, 3880, 3885, 3890, 3908, 3939, 3945, 3948, 3953, 3956, 4125, 4143, 4154, 4198, 4242, 4251, 4260, 4276, 4285 with 1 shot per zone. Fraced with 68,000# 20/40 sand and 70,560 gallons water. No ball sets dropped. Flushed with 4662 gallons water.
*Perfed 4382, 4452, 4456, 4465, 4470, 4474, 4478, 4480, 4490, 4495, 4500, 4525, 4542, 4564, 4650, 4672, 4734, 4764, 4788, 4826' with 1 shot per zone. Fraced with 44,000# 20/40 sand and 46,538 gallons water. No ball sets dropped. Flushed with 5502 gallons water.



NOV 11 1976

18. I hereby certify that the foregoing is true and correct

SIGNED A. G. Buico

TITLE Drilling Clerk

DATE 11-10-76

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side