

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SP 078132

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

A. L. Elliott "D"

9. WELL NO.

1A

10. FIELD AND POOL, OR WILDCAT

Blanco Masaverde11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA**SE 1/4 NW 1/4 Section 12,
T-29-N, R-9-W**

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico1. ☐ OIL
WELL ☐ GAS
WELL ☒ OTHER

2. NAME OF OPERATOR

Anoco Production Company

3. ADDRESS OF OPERATOR

501 Airport Drive, Farmington, NM 874014. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface**1710' FWL & 1590' FWL, Section 12, T-29-N, R-9-W**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3994' est. GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:


TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐**Spud & Set Casing** ☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud 12-1/4" hole on 3-17-77. Drilled to 271' and set 9-5/8" H-40 casing at 269' with 280 sacks Class B cement and 2% CaCl₂. Circulated good cement. WOC and pressure tested casing to 500 PSI, OK. Drilled 8-3/4" hole to 3025'. Set 7" K-55 casing at 3025' with 525 sacks Class B cement, 6% gel, 2 pounds medium Tuff Plug per sack. Cement did not circulate. Squeezed bradenhead with 100 sacks Class B and 2% CaCl₂. WOC. Pressure tested casing to 800 PSI, OK. Drilled 6-1/4" hole to 5125'. Set 4-1/2" K-55 liner from 2822-5125' with 200 sacks Class B 50:50 pos, 6% gel, 2 pounds medium Tuff Plug per sack and 0.2% friction reducer. Followed with 75 sacks Class B 50:50 pos and 6% gel. Reversed out trace cement.



APR 4 1977

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Area Adm. Supvr.

DATE

4-1-77

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.