

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR
Amoco Production Company

3. ADDRESS OF OPERATOR
501 Airport Drive Farmington, NM 87401


4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 940' FNL x 1000' FEL, Section 15,
AT TOP PROD. INTERVAL: Same T29N, R9W
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Completion ☐

SUBSEQUENT REPORT OF:



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

5. LEASE
SF-078132

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
A. L. Elliott "C"

9. WELL NO.
4

10. FIELD OR WILDCAT NAME
Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
NE/4, NE/4, Section 15, T29N, R9W

12. COUNTY OR PARISH
San Juan

13. STATE
NM

14. API NO.
30-045-23346

15. ELEVATIONS (SHOW DF, KDB, AND WD)
5950' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Completion operations commenced on 3-24-80. Total depth of the well is 7170' and plugback depth is 7145'. Perforated intervals from 7072' to 7122' with 2 SPF, with a total of 30 holes of 1/2" in diameter. Sand-water fraced with 55,617 gallons of frac fluid and 174,000# of sand. Perforated intervals from 6894' to 6991' with 2 SPF, with a total of 24 holes of 1/2" in diameter. Sand-water fraced with 61,500 gallons of frac fluid and 207,000# of 20-40 sand. Landed 2-3/8" tubing at 7133'. Swabbed the well and released the rig on 4-1-80.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED E. E. Smith TITLE Dist. Adm. Supvr. DATE 4-18-80

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACCEPTED FOR RECORD

APR 28 1980

*See Instructions on Reverse Side

NMOCCL

BY [Signature]
FARMINGTON DISTRICT