

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 080245-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

-----

7. UNIT AGREEMENT NAME

None

8. FARM OR LEASE NAME

L.V. Hamner "A"

9. WELL NO.

No. 1A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesaverde

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREASec. 21 - T29N - R9W  
N.M.P.M.

12. COUNTY OR PARISH

San Juan

13. STATE

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS  
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR D. J. Simmons

3. ADDRESS OF OPERATOR 3815 McCart Street  
Fort Worth, Texas 761104. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface 1720' FNL - 1760' FWL  
Sec. 21 - T29N - R9W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5619 GR 5632 KB

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐Set Surf, Intermed, & liner ☒(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* The above captioned well was spudded at 9:45 PM on 2-26-79 and

a 13 3/4" surf. hole was mud drilled to approx. 275'. At 4:45 AM on 2-27-79 approx. 249' of 9 5/8" 36# surface casing was set at 263' (KB) &amp; cemented with 220 sx of Cl. B cement &amp; 2% Calcium Chloride. Cement circulated to the surface.

On 2-27-79, prior to drilling out from under surface, a Shaffer 10" - 900 Series, hydraulic closing, double ram (pipe rams & blind rams), 6000 psi test blowout preventer was installed on the 9 5/8" surface casing and the casing was pressure tested to 600 psi and held steady for 30 min. Then, at approx. 1:45 PM a 8 3/4" hole was commenced and mud drilled below surface casing to approx. 3300' which was reached at approx. 12:15 AM on 3-2-79. Conditioned hole and ran intermediate string of 7" 20# K-55 casing to a depth of 3295'. 7" casing was cemented with 410 sx of 50-50 Poz & 150 sx of class B cement. Plug down at 10:30 AM 3-2-79. On 3-3-79 started drilling below 7" with natural gas and drilling a 6 1/4" hole in this manner to the logger's TD of 4815', reached at 4:45 AM on 3-4-79. Ran Induction-Gamma & Compensated Density logs on 3-4-79. On 3-4-79 ran 38 jts. of Range 3, 4 1/2" 10.5# K-55 csg. (liner), casing shoe set at 4815' with insert float set approx. 36' above shoe. TIW liner hanger (top of liner) set at 3126'. Liner was cemented with 230 sx of 50-50 Pozmix cement. Plug down at approx. 5:45 PM 3-4-79, float held OK: Formation tops: Surf. Nacimiento, Ojo Alamo 1060, Fruitland 1726, Pictured Cliffs 2060, Cliff House 3766, Menefee 3830, Point Lookout 4336, T.D. 4815.

18. I hereby certify that the foregoing is true and correct

SIGNED

Ashton B. Geren, Jr.

Manager &amp; Supt. for:

TITLE D.J. Simmons

DATE March 30, 1979

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

\*See Instructions on Reverse Side

