30-045-23532

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

Thus form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator BURLINGTON RESOURCES OIL & GAS CO.								Lease MIMS STATE COM			Well No. 1A
Location of Well:	TT '4	_									
of Well:	Unit	D	Sect	16	Twp.	029N	Rge.	009W	County	SAN JUAN	
			NAME OF	RESERVOI	R OR POO	DL	T	YPE OF PROD.	METH	OD OF PROD.	PROD. MEDIUM
	 						_	(Oil or Gas)	(Flow	or Art. Lift)	(Tbg. or Csg.)
Upper Completion	PICTURED CLIFFS							Gas	Flow		Tubing
Lower Completion	MESA	VERD	E	-			Gas		Flow		Tubing
					PRE-	FLOW SHUT-I	N PRES	SURE DATA	_1		
Upper	Hour, date shut-in Length of time shut-in									an on Ma	
Completion	9/4/99			120 Hours			'	361		Stabilized? (Yes or No)	
Lower Completion	9/4/99			72 Hours			173				
						FLOW TE	ST NO.				
Commenced	at (hour,	late)*			9/7/99			Zone producing	(Unper or I	nwer)	11.
TIME	LAPSED TIME		PRESSURE			PROD. ZONE	(opper or D		Upper		
(hour,date)	SINCE*		Upper Completion Lower Completion		Lower Comp			REMARKS			
9/8/99	96 Hours		142	2	173						
9/9/99	120 Hours		147		173			the second secon			
								7. /			
									N.	CCI	2 7 1999
									-	Mis (4)	Mac BITTS
								D.	D.Eto &		
roduction rate	during tes	t	I.						l		
il:	В	OPD ba	sed on		Bbls. in		Hours.		Grav.		GOR
as:			1	MCFPD; Tes	ted thru (C	rifice or Meter)): 				
					MID-T	FST SHI IT.IN	DD Ecci	DE DATA			
Upper Completion	Hour, da	MID-TEST SHUT-IN PI Tour, date shut-in Length of time shut-in					SI press. psig Stabilized? (Ye			or No)	
	Hour, date shut-in Ler			Length of t	ength of time shut-in		SI pre	ss. psig	S	Stabilized? (Yes or No)	

(Continue on reverse side)

FLOW TEST NO. 2 Zone producing (Upper or Lower): Commenced at (hour, date)** PRESSURE PROD. ZONE REMARKS LAPSED TIME TEMP. **Lower Completion** (hour, date) Upper Completion Production rate during test Oil: ______BOPD based on _____Bbls. in ____Hours ____Grav. ____GOR ____ MCFPD: Tested thru (Orifice or Meter): Remarks: I hereby certify that the information herein contained is true and complete to the best of my knowledge OCT 27 1999 __19 _____ Burlington Resources Operator Approved ___ New Mexico Oil Conservation Division ORIGINAL SIGNED BY CONVENIENT PERSON Title Operations Associate

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Title

BEPUTY OIL & GAS INSPECTOR, DIST. #3

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- $5. \quad \mbox{Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.$
- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

Date Friday, October 08, 1999

- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals thring the first hour thereof, and at hourly intervals threafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas thal completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).