This form is <u>not</u> to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

					11200 11-0			13301	Weell	
		Tenneco Oi	1 Con	ipa ny	L	eas e		Florance	No. 608	
Location				- 0.01	n -	_	011	Country		
i Well:	Unit	L_Sec]		wp •	Type of Prod	• —	Met.bod	County	Prod. ed:	
	Nan	ne of Resen	rvoir	or Pool		(1	Flow or	Art. Lift)		
per apletion		Fruitland ·			Gas		Flowing		C≩Si	
√we r	Pictured Cliff				Gas	Flowing		vina	"abi	
Compression					FLOW SHUT-IN PRI			ring	Pubi 🖯	
Upper Hour, date 9/2/79 Length of						SI press.		5S•	Stabilied?	
mpl Shut-in 10:00 a.m.			m		ut-in 8 days		psig	390	(Yes or No) S	
ower Hour, date 9/2/79				Length	of		SI pre	88.	Stabillized?	
ompl Si	nut-in	10:00 a.	<u>m. </u>	time sh	ut-in 8 days	<u> </u>	psig	625	(Yes or No)	
FLOW TEST NO. 1 Commenced at (hour, date) × 9/10/79 10:30 a.m. Zone producing (Upper or Lower): 1 er Time Lapsed time Pressure Prod. Zone										
Time	La (III	psed time	7 10	Pre	ssure	Pro	d. Zone	oddoing (oppo	1 OI MONEY ! G	
hour, dat		since* Uppe		r Compl.	Lower Compl.	Temp.		Rem	Remarks	
9/10/79 0:45 a	m.	15 mins.	390	<u> </u>	182					
:00 a.	m.	30 mins	390	<u> </u>	141					
<u>1:15 a.</u>	m.	. 45 mins) ·	104					
11:30 a.	a.m. l hour		390		72		·			
12:30 p.	m.	2 hours	390) .	50					
1:30 p.m)	36					
Production	rate	during tes	st Spod (~ ~	Phle in		Hre	s. Gra	v. GOR	
Oil: BOPD based on Bbls. in Hrs. Grav. GOR Gas: 669 MCFPD; Tested thru (Orifice or Meter): AOF										
				MID-	TEST SHUT-IN PR	ESSU	RE DATA			
Upper How				Length			SI pres		Stabilized?	
			time shut-in Length of			SI press.		(Yes or No) Stabilized?		
wer Hour, date Length Shut-in time sh					psig	1 /				
.511 51	140 111			011110 011	FLOW TEST N	0. 2				
menced	menced at (hour, date)**					Zone producing (Upper or Lower):				
Time	La	Lapsed time Pres			sure Prod. Zone Lower Compl. Temp.					
nour, dat	e) s	ince **	uppei	r compr.	FOMEL COUNT!		emb•	Tton		
			-							
			<u> </u>							
									The second secon	
								1	, da	
·				, , , , , , , , , , , , , , , , , , ,						
duction	rate	during tes	st		<u> </u>	·				
duction rate during test 1: BOPD based on MCFPD; Tested					Bbls. in_	Bbls. in Hrs.			Grav. GOR	
as:			MCFPI	D; Teste	d thru (Orifice	or l	Meter):	· · · · · · · · · · · · · · · · · · ·		
REMARKS:_						,			Same Const.	
				•					•	
I hereby (that the 1 5 1979		rmation	•	•			the best of my	
Approved:		19		Operator <u>Tenneco Oil Company</u>						
New Mexico Oil Conservation Commission Original Signed by FRANK T. CHAVEZ						By <u>Harold M. Kaulf</u> Harold Korell Title Division Engineer				
TEPLEY OIL & GAS INSPECTOR, DIST. #3						Date September 27, 1979				
TITLE UL &	#3		Date	Dave Schooling 1919						

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Commission.
- At least 72 hours prior to the commencement of any packer leakage test the operator shall notify the Commission in writing of the exact time the test is to be consenced. Offset operators shall also be so solified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided because that they need not remain shut-in wore than seven days.
- 4. For Fiow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: If, on an initial packer leskage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shutin, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak wis indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3-hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervalr thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges, the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Commission on Northwest New Mexico Packer Leakage Test Form Revised 11-1-58, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only). A pressure versus time curve for each zone of each test shall be constructed on the reverse side of the Packer Leakage Test Form with all deadweight pressure points taken indicated thereon. For oil zones, the pressure curve should also indicate all key pressure changes which may be reflected by the recording gauge charts. These key pressure changes should also be tabulated on the front of the Packer Leakage Test Form.

