

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Amoco Production Company	8. Farm or Lease Name Heath Gas Com "J"
3. Address of Operator 501 Airport Drive Farmington, NM 87401	9. Well No. 1E
4. Location of Well UNIT LETTER <u>F</u> , <u>1820</u> FEET FROM THE <u>North</u> LINE AND <u>1460</u> FEET FROM THE <u>West</u> LINE, SECTION <u>9</u> TOWNSHIP <u>29N</u> RANGE <u>9W</u> NMPM.	10. Field and Pool, or Wildcat Basin Dakota
15. Elevation (Show whether DF, RT, GR, etc.) 5703' GL	12. County San Juan

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK

TEMPORARILY ABANDON

PULL OR ALTER CASING

OTHER

PLUG AND ABANDON

CHANGE PLANS

SUBSEQUENT REPORT OF:

REMEDIAL WORK

COMMENCE DRILLING OPNS.

CASING TEST AND CEMENT JOB


OTHER Spud & Set Casing

ALTERING CASING

PLUG AND ABANDONMENT

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 12-1/4" hole on 11-17-79 and drilled to 301'. Set 9-5/8", 32.3# surface casing at 300' on 11-18-79 and cemented with 310 sx class "B" Neat cement containing 2% CaCl₂.
 Drilled 8-3/4" hole to 2561' and set 7", 20# intermediate casing at 2561' on 11-21-79. Cemented with 450 sx class "B" Neat cement containing 50:50 Poz, 6% gel, 2# Medium tuf plug per sx, and 0.8% fluid loss additive. Tailed in with 100 sx class "B" Neat cement.
 Drilled 6-1/4" hole to TD of 6861' and set 4-1/2", 11.6# production casing at 6860' on 11-21-79. Cemented with 370 sx class "B" Neat cement containing 50:50 Poz, 6% gel, 2# Medium tuf plug per sx and 0.8% fluid loss additive. Tailed in with 100 sx class "B" Neat cement.
 No DV tools were set on the above cementing programs.
 Rig released on 12-28-79.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E. E. SVOBODA Original Signed By
 TITLE Dist. Adm. Supvr.
 DATE 1-10-80

APPROVED BY Original Signed by FRANK T. CHAVEZ
 TITLE DEPUTY OIL & GAS INSPECTOR, DIST. 33
 DATE JAN 14 1980

CONDITIONS OF APPROVAL, IF ANY: