

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other Wildcat  
well well  
2. NAME OF OPERATOR  
Amoco Production Company  
3. ADDRESS OF OPERATOR  
501 Airport Dr., Farmington, NM 87401  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1530' FSL x 980' FWL  
AT TOP PROD. INTERVAL: Same  
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) Completion

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
SF 076337  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
W. D. Heath "A"  
9. WELL NO.  
14  
10. FIELD OR WILDCAT NAME  
Wildcat  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA NW/4, SW/4, Section 9, T29N, R9W  
12. COUNTY OR PARISH San Juan  
13. STATE NM  
14. API NO.  
30-045-23902  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5732' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

MAY 13 1981  
OIL CON. COM.  
DIST. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Completion operations commenced again on 3/16/81. Total depth of the well is 2247' and the plugback depth is 2135'. Perforated intervals from 1116'-1120' and 1150'-1154', 1466'-1470' and 1500'-1506', with 2 spf, a total of 36, .38" holes. Squeezed perforated intervals with 100 sacks of Class B neat cement. Fraced formation with 21,500 gallons of foam and 33,500 pounds of 10-20 sand. Tripped out of hole with 2 7/8" tubing and landed 2 7/8" tubing at 1528'. Swabbed the well and started to pump on 4/2/81. Released the rig on 4/3/81.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED E. E. SVOBODA TITLE Dist. Adm. Supvr. DATE May 7, 1981

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

NMOCC