

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

5. LEASE
SF-078132

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
A. L. Elliott "B"

9. WELL NO.
8

10. FIELD OR WILDCAT NAME
Blanco Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SW/4, NE/4, Section 10, T29N, R9W

12. COUNTY OR PARISH 13. STATE
San Juan NM

14. API NO.
30-045-24202

15. ELEVATIONS (SHOW DF, KDB, AND WD)
5932' GL

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR

Amoco Production Company

3. ADDRESS OF OPERATOR

501 Airport Drive, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1910' FNL x 1490' FEL

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐


☐

☐

☐

Completion

(NOTE: Report results of multiple completion or zone change on Form 9-331-C)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Completion operations commenced on 7-22-80. Total depth of the well is 2745', and plug back depth is 2683'. Perforated interval from 2658-2648' & 2610-2545', with 2 SPF, a total of 150, .38" holes. Foam fraced with 56,000 gal of foam frac fluid, and 100,000# of 20-40 sand. Perforated interval from 2506-2502' & 2382-2376', with 2 SPF, a total of 20, .38" holes. Foam fraced with 34,000 gal of foam frac fluid, and 60,000# of 20-40 sand. Landed 2-3/8" tubing at 2506'. Swabbed the well and released the rig on 8-1-80.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct.

SIGNED E. E. [Signature] TITLE Dist. Adm. Supvr DATE 8-19-80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

AUG 22 1980

FARMINGTON DISTRICT

*See Instructions on Reverse Side

BY