

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☒ well ☐ other

2. NAME OF OPERATOR  
Tenneco Oil Company

3. ADDRESS OF OPERATOR  
P. O. Box 3249, Englewood, CO 80155

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1750' FSL 1510' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
SF-078049

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Hughes A

9. WELL NO.  
4E

10. FIELD OR WILDCAT NAME  
Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 34, T29N R8W


12. COUNTY OR PARISH  
San Juan

13. STATE  
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6485' Gr.

(NOTE: Report results of multiple completion or zone change on Form 9-330)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

4/20/82 - WOC, drill out and unload hole. Dry up and resume drlg.  
4/23/82 - TFB. Lost cone, WO junk basket, fish w/magnet. TOO H w/cone. TIH w/new bit.  
4/25/82 - Drill to TD @ 7578' @ 7:30 a.m. 4/25/82. Log w/GO. Lay down drill pipe and drill collars. RU and run 13 jts 4-1/2" 11.6# K-55 csg and 79 jts 4-1/2" 10.5# K-55 csg. set @ 7576'. TOL @ 3456'. Cmt w/350 sx Cl-B + 2% econolite and .6% HALAD-9. Tail by 150 sx Cl-B + .5% HALAD-9 + .5% CFA 2. TOC @ 3456'. PD @ 11:30 p.m. Circ 13 bbls flush to surface.  
4/26/82 - NDBOP. Rig released at 6:00 a.m. on 4/26/82.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Denise Wilson TITLE Production Analyst DATE 4/29/82  
Denise Wilson

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

\*See Instructions on Reverse Side

RECORDED

MAY 1 1982  
FACILITY RECORD  
BY 222