

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

Tenneco Oil Company

3. ADDRESS OF OPERATOR

Box 3249 Englewood, CO 80155

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1,190' FSL, 2130' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other) Log Well

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

JUN 14 1982

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6/7/82 MIRUSU. NDWH, NUBOP. Tallyed & RIH w/120 jts. tbg, bit sub & 3-7/8" bit.
6/8/82 RIH w/ balance of tbg, tagged SD fill at 5940'. Drld to PBTD at 6058'.
PT csg. to 3500 psi, OK. Circ. hole w/2% KCL wtr. Pld up to 6006'. Spotted
500 gal. 7½% DI HCL across perms. POOH w/tbg and bit. RU Schlumberger. Ran
GR/CCL/TDT fr. 6058' to 5500', 4600' to 3700', and 3400' to 2900'. Closed
locked rams.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Denise Wilson TITLE Prod. Analyst DATE 6/11/82

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY

TITLE _____

DATE _____

ACCEPTED FOR RECORD

JUN 15 1982

FARMINGTON DISTRICT

BY Smh

*See Instructions on Reverse Side

NMOCC