Budget Bureau No. 1004-0135 UNITED STATES

BUBMIT IN TRIPLICATES

Other Instructions of re
Other Inst Form 3160-5 (November 1983) Expires August 31, 1985 5. LEASE DESIGNATION AND SERIAL NO. (Formerly 9-331) BUREAU OF LAND MANAGEMENT SF-076337 6. IF INDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT--" for such proposals.) 7. UNIT AGREEMENT NAME WELL X WELL . 8. PARM OR LEASE NAME 2. NAME OF OPERATOR W. D. Heath "A" Amoco Production Company 9. WELL NO. 3. ADDRESS OF OPERATOR 501 Airport Drive, Farmington, NM 87401

LIGHT AT THE STATE OF WELL (Report location clearly and in accordance with any State regular mental at surface. 10E 10. PIELD AND POOL, OR WILDCAT Basin Dakota 11. SEC., T., B., M., OR BLE. AND SURVEY OR AREA 1760' FSL x 790' FEL DEC 10 1964 BUREAU OF LAND PARAGEMENT NE/SE Sec. 17, T29N, R9W 15. ELEVATIONS (Show whether Dr. Rt. GR. etc.) San Juan 56921 GR Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data 16. NOTICE OF INTENTION TO: PULL OR ALTER CASING REPAIRING WELL TEST WATER SHUT-OFF WATER SHUT-OFF PRACTURE TREATMENT MULTIPLE COMPLETE (Other) Completion ABANDON MENTS RHOUT OR ACIDIZE REPAIR WELL CHANGE PLANS (Nors: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other) 17 DESCRIBE PROPOSED OF COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and sones pertinent to this work.) \* Moved in and rigged up service unit 11-17-84. Total depth of the well is 6700' and plugback depth of the well is 6659'. Pressure tested production casing to 3500 psi. Perforated the following intervals: 6515'-6508', 6542'-6536', 6590'-6582', 6608'-6602', 6634'-6626', 6650'-6643', 4 Jspf, .37'' in diameter. Fraced interval 6508'-6650' with 78,500 gal. 75 quality foam and 155,000#20-40 sand. Landed 2-3/8" tubing at 6418' and released the rig on 11-28-84. with that the foregoing is true and correct Adm. Supervisor Original way we by TITLE B. D. Shaw derai or State office use)

Form approved.

\*See Instructions on Reverse Side

APPROVED BY

CONDITIONS OF APPROVAL IF ANY: