Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
. Expires: March 31, 1993

Conditions of approval, if any:	JUN 16 1998
Approved by Title	Date
Title ENGINEER (This space for Federal or State office use)	ACCEPTED FOR RECORD
14. I hereby certify that the foregoing is true and correct Signed V _	Date 6/5/98
Diet. 3	
OIL COIL DIN	
JUN 1 8 1998	9. H. F.
DEGENVE	JONES - 8 - W. BLANCE
SEE ATTACHED MORNING REPORT.	98 0 70
13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of stagive subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*	
Other SPUD, RUN CASING, CEMENT SURFACE CAS	Dispose Water
Casing Repair Final Abandonment Notice Altering Casing	Water Shut-Off Conversion to Injection
Notice of Intent Recompletion Subsequent Report Plugging Back	New Construction Non-Routine Fracturing
TYPE OF SUBMISSION Notice of Intent Abandonment	Change of Plans
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REP	
Sec. K23, T29N, R9W	SAN JUAN COUNTY, NM
1625 FSL & 1530 FWL	11. County or Parish, State
PO BOX 168 FARMINGTON, NM 87499 (505)326-2659 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	BLANCO MESA VERDE
3. Address and Telephone No.	30-045-29595 10. Field and Pool, or Exploratory Area
ROBERT L. BAYLESS, PRODUCER LLC	9. API Weil No.
Oil X Gas Well Other 2. Name of Operator	8. Well Name and No. SIMMONS E #2R
1. Type of Well	
SUBMIT IN TRIPLICATE	7. If Unit or CA, Agreement Designation
Do not use this form for proposals to drill or to deepen or reentry to a different reservo Use "APPLICATION FOR PERMIT—" for such proposals	orr.
SUNDRY NOTICES AND REPORTS ON WELLS	SF-080000-A 6. If Indian, Allottee or Tribe Name
BUREAU OF LAND MANAGEMENT	5. Lease Designation and Serial No.

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States PARTHULTURE INTERIOR OF THE PROPERTY OF THE PRO

ROBERT L. BAYLESS

Simmons E #2R 1625 FSL & 1530 FEL SECTION 23, T29N, R9W

MORNING REPORT-DRILLING

6/4/98

Move Aztec Rig #433 to location and rig up. Spud 12 ¼" surface hole at 4:30 pm, 6/3/98. Drill to 145 feet. Run deviation, 1/2° at 145 feet. Trip out of hole and run 3 joints (125.70 feet) of 9 5/8" 36 #/ft ST&C casing, landed at 135 feet. Rig up Cementers Inc. and cement casing with 100 sacks (118 cf) of Class G with 4% CaCl. Good returns throughout job with 9 bbls circulated to pit. Plug down at 9:30 pm, 6/3/98. WOC for 4 hours. Nipple up wellhead and BOP. Pressure test BOP and choke manifold to 100 psi for 30 minutes, held OK. Trip in hole to drill cement.