-L. G. Truby

i-E.P.M.G.-(Galloway)

l-Phillips Petroleum(Smith)

l-W. R. Johnston

l-File

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Poo	1 <u>B</u>	lanco	<u> </u>		·	<u> </u>	Pormation	<u>n</u>	Nes	ave	rde	_County_	Rio A	r ri b	3
Ini	tial	X	<u> </u>		Annu	ai		Sp	ecial			Date of	Test	2- 13	-57
							line					Wel			
								_				lfic North			
													,		
Proc	ducir	ng Th	ינויז:	Ca	sing		 ጥ	uhing			Type We		_Bar • r r	••••	
Dat.e	ല വീ	Comp	let.	ion•			Psoke	an		Sing	le-Brade	ell enhead-G. oir Temp.	G. or	G.O.	Dual
	• • •	ОСПЕР	200.			······································	. GOR		RVED DA'		_neserve	TI Temp.		<u>,</u>	
Poet	tod 1	المعمارة	a h	(Dwa		Ob = 1 - = \	/38 mmma_				_				
			RII.		Flow D		(Men. 1.	/ 5 m				Type Tap		 -	
\Box				(Ch	oke)	Press	. Diff.	Temp			Data Temp.	Casing D		†	
No.		Line Size		•	fice) ize	psig	h _w	o _F .	ps:	ig	o _F .	psig	[⊃] F.		of Flow Hr.
SI .				3/	<u>, </u>	331.		<u> </u>	1107			1122		1	
2. 3.							 	 	331		670	925	 		3
↓. 5.											······································		 	#	
<u>) • </u>		·		· · · · · ·			<u> </u>			l		<u> </u>	1		
T	C	Coefficient		P	Pressure Pressure		- 1		Gravity				Rate of Flow		
10.	(24-Hour) $\sqrt{h_{wp}}$		o _f	psia	l .	actor ^F t		Factor F _g	Factor F _{pv}		Q-MCFPD @ 15.025 psia				
2. 3. 4.	14.1605			343		0.9933		0.96		1.035		4793			
										-		1.034			
avi	ity c	f Lic	quid		n Ratio				CALCUI 1. g.	ATIC	Speci Speci	fic Gravi fic Gravi 1134	ty Flo	wing	Fluid
0.	P _w	(psia	a)	P	E F	,Q	(F _c Q) ²	2	$(F_cQ)^2$ $(1-e^{-s})$!	9 37 P _w 2	$P_c^2 - P_w^2$		al.	Pw Pc
										87	7.97	407.99			
										_				$-\frac{1}{1}$	3.15 19
•			\perp			220			77	1/0	26.CE			\Box	
OMF	ANY_	Paci	enti M c	Lal:	thwest	Pipel	ine Corp	MCFP oratio	υ; n <u>• (</u> 2	7/2	•3077				
GEN	IT an	d TI	PLE_	West C. 1	Broads	my, r	armingto ell Test	n, Nev	MESCI CO				Zit	W	10
	NESSE PANY	D				_							KIT	n.	
J111							£	R.	EMARKS				· F.F.	- 186	COM
								4 · 1				,	OIL	DIS COL	COM.

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure (P_W) . MCF/da. @ 15.025 psia and 60° F.
- P_c 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- PwI Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt- Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- P_{f} Meter pressure, psia.
- $h_{\mbox{w}}$ Differential meter pressure, inches water.
- Fg Gravity correction factor.
- Ft Flowing temperature correction factor.
- F_{pv} Supercompressability factor.
- n I Slope of back pressure curve.

Note: If $P_{\rm W}$ cannot be taken because of manner of completion or condition of well, then $P_{\rm W}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\rm t}$.

OIL CONSERVAT	TION COMMIS	SSION							
AZTEC DISTRICT OFFICE									
No. Copies Received 3									
DISTRIBUTION									
Secretary and the secretary an	i io. Dagrode								
Company	†								
Santa Fo	1								
Piteration Office									
State Land Office									
U. G. P. S.	/								
Transporter									
File	/								