


N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico



Grid for well location with an 'X' in the 4th row, 1st column.

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES LOCATE WELL CORRECTLY

J. Glenn Turner

State

Company or Operator Lease Well No. 4 in NW 1/4 of Sec. 36, T. 30 N

R. 6 W, N. M. P. M. Blanco Field, Rio Arriba County.

Well is 1,650 feet from south line and 990 feet from west line of 36

If State land the oil and gas lease is No. E - 347 Assignment No. 18

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is J. Glenn Turner Address 17th floor - Mercantile Bldg. Dallas 1, Texas.

Drilling commenced April 1, 1953 Drilling was completed July 8, 1953

Name of drilling contractor McConnell Drilling Corp. Address Farmington, N. M.

Elevation above sea level at top of casing 6,567 feet.

The information given is to be kept confidential until 19

Gas SANDS OR ZONES

No. 1, from 5,340 to 5,880 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

Table with columns: SIZE, WEIGHT PER FOOT, THREADS PER INCH, MAKE, AMOUNT, KIND OF SHOE, CUT & FILLED FROM, PERFORATED TO, PURPOSE. Includes data for 10-3/4 and 7 inch casings.

MUDDING AND CEMENTING RECORD

Table with columns: SIZE OF HOLE, SIZE OF CASING, WHERE SET, NO. SACKS OF CEMENT, METHOD USED, MUD GRAVITY, AMOUNT OF MUD USED. Includes data for 13-3/4 and 9 inch holes.

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

Table with columns: SIZE, SHELL USED, EXPLOSIVE OR CHEMICAL USED, QUANTITY, DATE, DEPTH SHOT OR TREATED, DEPTH CLEANED OUT. Includes data for solidified nitro glycerin.

Results of shooting or chemical treatment I.P. 3,970 MCF after three hours open flow through casing. Shut in casing pressure - 1142 # after 9 days.

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from Surface feet to 5,975 feet, and from feet to feet.

Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to producing 19

The production of the first 24 hours was barrels of fluid of which % was oil; % emulsion: % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Well shut in Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

Driller Driller

Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Farmington, N. M. August 20, 1953. Place Date

Name Beeson Neal, Agent in Farmington Position

Representing J. Glenn Turner Company or Operator.

Address Box 728 - Farmington, New Mexico.

Home Office: 17th fl. - Mercantile Bank Bldg. Dallas 1, Texas.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	2,760		
0	2,760	2,760	Tertiary sands and shales
2,760	3,200	440	Kirtland
3,200	3,509	309	Fruitland
3,509	3,620	111	Pictured Cliffs
3,620	5,352	1,732	Lewis
5,352	5,410	58	Cliff House
5,410	5,697	287	Menefee
5,697	5,870	173	Point Lookout
	5,975		Total depth

OIL CONSERVATION COMMISSION
AZTEC DISTRICT OFFICE

No. Copies Received

DISTRIBUTION

	No. Copies	
Geologist	1	
Cartographer	1	
Production Office		
State Land Office		
U. S. G. S.	1	
Transporter	1	
File		<input checked="" type="checkbox"/>