(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Land Office New Mexico
Lease No. 2151
Unit bitley
(San Juan 30-6 Unit)
14-08-001-530

NOTICE OF INTENTION TO DRILL	
Name	SUBSEQUENT REPORT OF WATER SHUT-OFF.
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ASIDE
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSECUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSECUENT REPORT OF DE DRILLING OF DESCRIPTION
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSECUENT REPORT OF ARANDOMATAIN
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL DISTORY
NOTICE OF INTENTION TO ABANDON WELL.	
(INDICATE ABOVE BY CHECK MARI	K NATURE OF REPORT, NOTICE, OR OTHER DATA)
	August 11 , 19 53
Vell No. 3-B is located 1800 ft. from	m. S line and 1650 ft. from W line of sec. 33
G Sec. and Sec. No.) (Twp.)	74 N. M. P. M.
Till a a a	(Range) (Meridian)
(Field)	or Subdivision) (State or Territory)
	• • • • • • • • • • • • • • • • • • • •
ne elevation of the derrick floor above sea lev	1111 IU.
DETAI	ILS OF WORK
ate names of and expected depths to objective sands; show size	LS OF WORK AUG 1 4 1953 res, weights, and lengths of proposed casings; indicate mudding joint compared their important proposed work) U. S. GEOLOGICAL SURVEY
ing points, and all of	other important proposed work)
	FARMINGIUN, N. M.
It is intended to drill a to drilling the pay with gas circulate two quarts of S.M.G. per foot. To Casing Program: 9-5/5 at 160' with 12 7 at 4-36' with 50	randington, N. M. well with rotary tools thru the Messwerde, ion and to shoot the entire Messwerde with tall depth 5463'. 25 sacks of regular cement circulated to surface of sacks of regular cement.
It is intended to drill a to drilling the pay with gas circulate two quarts of S.H.G. per foot. To Casing Program: 9-5/5 at 160' with 12 7 at 4-36' with 50	well with rotary tools thru the Messverde, ion and to shoot the entire Messverde with tai depth 5463'.
It is intended to drill a drilling the pay with gas circulate two quarts of S.M.G. per foot. To Casing Program: 9-5/5 at 160° with 12 The Wg of Section 3	rankington, N. M. well with rotary tools thru the Messverde, ion and to shoot the entire Messverde with tal depth 5463'. 25 sacks of regular cement circulated to surface of sacks of regular cement. 33 is dedicated to this well.
It is intended to drill a drilling the pay with gas circulations two quarts of S.M.G. per foot. To Casing Program: 9-5/5 at 160' with 12 The Wg of Section 3 I understand that this plan of work must receive approval in w	randington, N. M. well with rotary tools thru the Messwerde, ion and to shoot the entire Messwerde with tall depth 5463'. 25 sacks of regular cement circulated to surface of sacks of regular cement.
It is intended to drill a drilling the pay with gas circulate two quarts of S.H.G. per foot. To Casing Program: 9-5/5 at 160' with 12 The Wg of Section 3	rankington, N. M. well with rotary tools thru the Messverde, ion and to shoot the entire Messverde with tal depth 5463'. 25 sacks of regular cement circulated to surface of sacks of regular cement. 33 is dedicated to this well.
It is intended to drill a drilling the pay with gas circulations the pay with gas circulations of S.H.G. per foot. To Casing Program: -5/5 at 160' with 12 -5/5 at 4-336' with 50 The Wg of Section 3	rankington, N. M. well with rotary tools thru the Messverde, ion and to shoot the entire Messverde with tal depth 5463'. 25 sacks of regular cement circulated to surface of sacks of regular cement. 33 is dedicated to this well.