

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

RECEIVED
MAR 25 1993

Type of Well
GAS

Name of Operator
Meridian Oil Inc.

Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

Location of Well, Footage, Sec., T, R, M
1750'FSL, 890'FWL Sec.31, T-30-N, R-7-W, NMPM

5. Lease Number
NM-012709
6. If Indian, All. or
Tribe Name
7. Unit Agreement Name
San Juan 30-6 Unit
8. Well Name & Number
San Juan 30-6 U #8
9. API Well No.
30-039-
10. Field and Pool
Blanco Mesa Verde
11. County and State
Rio Arriba Co, NM

1. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

- | | | |
|---|---|--|
| ☐ Notice of Intent | ☐ Abandonment | ☐ Change of Plans |
| ☒ Subsequent Report | ☐ Recompletion | ☐ New Construction |
| ☐ Final Abandonment | ☒ Plugging Back | ☐ Non-Routine Fracturing |
| | ☐ Casing Repair | ☐ Water Shut off |
| | ☐ Altering Casing | ☐ Conversion to Injection |
| | ☐ Other - | |

2. Describe Proposed or Completed Operations

- 02-27-93 MOL&RU. NU BOP. TOOH w/tbg. Set RBP @ 4478'. Load hole w/wtr. Ran CBL 3400-4478'. TOC @ 3950'. Ran free point.
- 02-28-93 Made chemical cut @ 2536'. LD 5 1/2" csg. TIH w/scrapers to 2520'. Set RBP @ 2497'. Ran CBL to 2536'. Cmt from 0-365', 2050-2536'.
- 03-01-93 Shot 2 squeeze holes @ 1920'. TIH w/retrievematic set @ 2200'. Spot 3 sx sand, pull to 1707'. PT annulus 750. Est rate 1.5 BPM @ 1500#. Squeeze w/100 sx Class "B" w/2% calcium chloride. WOC. Ran CBL 1830-1300'. No sign of squeeze cmt. TIH to 1830'. Start drlg @ 1860'.
- 03-02-93 Drl cmt 1860-1925'. Ran CBL 2000-1400'. Cmt 1870-1950'. PT csg 780#, leak off 300#/5 min. TIH to 1950'. Spot 50 sx Class "B" w/2% calcium chloride (1730-1950'). Pull to 1650'. Squeeze .5 bbl cmt into hole @ 1920'. Held 1000#. WOC. Shot 2 hoels @ 1575'. Set pkr @ 1395'. Est rate. Squeeze w/100 sx Class "B" w/2% calcium chloride, squeeze to 1600 w/75 sx in formation. Reverse out. WOC.

(cont'd on back)

I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Affairs Date 3/8/93

This space for Federal or State Office use)

APPROVED BY _____ Title _____

CONDITION OF APPROVAL, if any:

ACCEPTED FOR RECORD

Date

MAR 28 1993

FARMINGTON DISTRICT OFFICE

BY

NMOC

03-03-93 Drl cmt 1449-1595'. PT squeeze holes @ 1575' for 750#/30 min. Failed. TOO H. TIH to 1605'. Spot 50 sx Class "B" w/2% calcium chloride (1605-1385'). Pull to 1227'. Squeeze 2 bbl into hole @ 1575'. Held 1350 psi. WOC.

03-04-93 Drl cmt 1401-1980'. PT @ 1575' 750#/30 min, 1920' @ 750#/30 min, ok. Ran CBL 2040-1270'. TOO H w/BP. TIH to 2536'. Mill top of 5 1/2" csg smooth cut 7". TIH w/csg patch to top of cut off @ 2536'. Circ.

03-05-93 Set patch. PT 1000#/30 min, ok. Ran 56 jts 5 1/2", 15.5#, K-55 csg w/csg patch on btm, 2524' set @ 2536'. ND BOP. PU retrieving head. TIH to 4450'.

03-06-93 Ran 160 jts 2 3/8" tbg set @ 5009'. F nipple @ 4977'. ND BOP. NU WH. Released rig.