

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name San Juan 30-6 Unit
2. Name of Operator El Paso Natural Gas Company	8. Farm or Lease Name San Juan 30-6 Unit
3. Address of Operator Box 990, Farmington, New Mexico 87401	9. Well No. 89 (OWWO)
4. Location of Well UNIT LETTER H 1800 FEET FROM THE North LINE AND 990 FEET FROM THE East LINE, SECTION 36 TOWNSHIP 30N RANGE 6W N.M.P.M.	10. Field and Pool, or Wildcat Blanco Mesa Verde
15. Elevation (Show whether DF, RT, GR, etc.) 6818' GI	12. County Rio Arriba

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Squeeze, Case Cement, Perf & S/W Frac

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-2-71 cut off stuck tubing at 5675', pulled tubing.

6-3-71 Set cement retainer at 5489', squeezed open hole w/150 sacks of cement. Perforated squeeze hole at 3037', set cement retainer at 2948', squeezed through perf. w/125 sacks of cement.

6-8-71 T.D. 6379'. Ran 206 joints 4 1/2", 10.5#, KS production casing (6366') set at 6379' w/125 sacks of cement. W.O.C. 18 hours.

6-9-71 P.B.T.D. 6345'. Perf. 5962-74', 6026-38', 6058-82', 6094-6106', 6210-24' w/24 ~~XXX~~ SPZ Frac w/50,000# 20/40 sand, 48,300 gal. water, dropped 4 sets of 24 balls, flushed w/5880 gal. water. Dropped bridging ball to baffle and tested to 3500# O. K. Perf. 5632-38', 5650-60', 5670-76' w/20 SPZ. Frac w/40,000# 20/40 sand, 40,026 gal. water, dropped 2 ~~XXXX~~ sets of 20 balls, flushed w/3822 gal. water.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Original Signed F. H. WOOD TITLE Petroleum Engineer DATE June 23, 1971

APPROVED BY Donald R. G. by Henry C. Arnold TITLE SEAL FOR THE STATE OF NM DATE JUN 23 1971

CONDITIONS OF APPROVAL, IF ANY: