

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Phillips Petroleum Company

3. Address and Telephone No.

5525 Hwy. 64, NBU 3004, Farmington, NM 87401 (505) 599-3454

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

990 FNL & 1500' FEL
Section 35, T-30-N, R-5-W

5. Lease Designation and Serial No.

SE-078737 NM-012332

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 30-5 Unit

8. Well Name and No.

4

9. API Well No.

30-039-07745

10. Field and Pool, or Exploratory Area

Blanco Mesaverde

11. County or Parish, State

Rio Arriba, N.M.

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other TP&A

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Pull tubing, set cement retainer at +5725' and pump cement above and below retainer to permanently abandon MesaVerde. Fill liner with inhibited fluid, set a CIBP at + 5600' spot/dump bail 50' cement on top of CIBP, fill the wellbore with an inhibited fluid, and pressure test the casing to 500 psi to temporarily abandon the well. Well will be used for future Fruitland Coal recompletion.

Anticipate work to be completed in 1994. Will contact Mark Kelly 48 hours prior to commencing any abandonment operations.

See attached wellbore schematic for casing depths and perforations.

RECEIVED

JAN 28 1994

OIL CON. DIV

THIS APPROVAL EXPIRES FEB 01 1995

070 FARMINGTON, NM
JAN 18 AM 8:01

RECEIVED
BLM

14. I hereby certify that the foregoing is true and correct

Signed Ed Hasely Ed Hasely Title Environmental Engineer Date 1-14-94

(This space for Federal or State office use)

Approved by _____ Title _____ Date _____
Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NMOCD

APPROVED
JAN 28 1994
DISTRICT MANAGER

GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

SPECIFIC INSTRUCTIONS

Item 4—If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 5—Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

NOTICE

The Privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et. seq., 351 et. seq., 25 U.S.C. et. seq.; 43 CFR 3160.

PRINCIPAL PURPOSE — The information is to be used to evaluate, when appropriate, approve applications, and report completion of secondary well operations, on a Federal or Indian lease.

ROUTINE USES:

- (1) Evaluate the equipment and procedures used during the proposed or completed subsequent well operations.
- (2) Request and grant approval to perform those actions covered by 43 CFR 3162.3-2(2).
- (3) Analyze future applications to drill or modify operations in light of data obtained and methods used.
- (4)(5) Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions.

EFFECT OF NOT PROVIDING INFORMATION — Filing of this notice and report and disclosure of the information is mandatory once an oil or gas well is drilled.

The Paperwork Reduction Act of 1980 (44 U.S.C. 3501, et. seq.) requires us to inform you that: This information is being collected in order to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

This information will be used to report subsequent operations once work is completed and when requested, to obtain approval for subsequent operations not previously authorized.

Response to this request is mandatory for the specific types of activities specified in 43 CFR Part 3160.

BURDEN HOURS STATEMENT

Public reporting burden for this form is estimated to average 25 minutes per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management, (Alternate) Bureau Clearance Officer, (WO-771), 18 and C Streets, N.W., Washington, D.C. 20240, and the Office of Management and Budget, Paperwork Reduction Project (1004-0135), Washington, D.C. 20503.

PHILLIPS PETROLEUM COMPANY--FARMINGTON AREA

RKB @ 6935'
CHF @
GL @ 6927'

Date: July 27, 1993

Lease & Well No.: San Juan Unit 30-5 No. 4
Legal Description: 990' FNL, 1500' FEL, Section 35, T30N, R5W,
County: Rio Arriba State: NM
Field: Blanco Mesa Verde
Status: Shut in
Tbg.: 1" 1.7 & 1.8 lb/ft @ 6286'
Other: 1": 1823' 1.7 lb/ft Regular, 4452' 1.8 lb/ft EUE
Tubing perforations: 6244'-6286'

Date Drilled: 6/5/53

Hole/Casing Condition: The 5-1/2" slotted liner was run and liner hanger failed. The top of the 5-1/2" casing was never determined. A total of 696' if csg was run plus the liner hanger. Top of liner should approx. be 5644'. A string of 1" tubing was run. The tubing became stuck and parted during fishing operations. It is unclear from wellfile whether all of tbg was recovered. Another string was landed at 6286'.

10-3/4" @ 174'
21.63 lb/ft, SWSJ
TOC @ Surface
Circ. 195 sxs cmt

7" DV Tool set @ 3777'

Failed Float Liner Hanger @ ± 5644'

7" @ 5690'
20 lb/ft, J-55 (2037')
23 lb/ft, J-55 (3635')
First Stage: 300 sxs cmt (TOC @ 4685')
Second Stage: 150 sxs cmt (TOC Unknown)
8-3/4" Hole

Mesa Verde Perforations

5770'-6350' (Shot with 1880 qts SNG)

5-1/2" @ 6350'
15.5 lb/ft, J-55
No cement

TD @ 6134'
PBD 6320'