





LOCATE WELL CORRECTLY

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYU. S. LAND OFFICE
SERIAL NUMBER
LEASE OFNew Mexico
DEC 8 1955
U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

LOG OF OIL OR GAS WELL

Company PACIFIC NORTHWEST PIPELINE CORP. Address 413 1/2 W. Main, Farmington, New Mexico
Lessor or Tract Unit 30-6 Field Blanco State New Mexico
Well No. 15-29 Sec. 29 T. 30N R. 7W Meridian N.M.P.M. County Rio Arriba
Location 1700 ft. N. of Sec. Line and 900 ft. E. of Sec. Line of Sec. 729 Elevation 6289.20
(Derrick floor relative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Signed _____ Original signed by T. A. Dugan

Date November 26, 1955Title District Engineer

The summary on this page is for the condition of the well at above date.

Commenced drilling October 12, 19 55 Finished drilling November 3, 19 55

OIL OR GAS SANDS OR ZONES

(Denote gas by G)

No. 1, from 4936 to 5456 G No. 4, from _____ to _____

No. 2, from _____ to _____ No. 5, from _____ to _____

No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

No. 1, from _____ to _____ No. 3, from _____ to _____

No. 2, from _____ to _____ No. 4, from _____ to _____

CASING RECORD

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From—	To—	
10-3/4	32.75	8 rd.	J & L	187.51					
8-1/2	26.00	8 rd.	J & L	100.00					
7-5/8	24.00	8 rd.	J & L	100.00					
5-1/2	14.00	8 rd.	J & L	100.00					
5-1/2	14.00	8 rd.	J & L	100.00					

MUDDING AND CEMENTING RECORD

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
10-3/4	281.42	160 cu. ft.	Malliberton		
7-5/8	388.00	160 cu. ft.	"		
5-1/2	549.00	160 cu. ft.	"		
5-1/2	549.00	160 cu. ft.	"		

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth set _____

Adapters—Material _____ Size _____

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out

TOOLS USED

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

DATES

November 3, 1955 Put to producing _____, 1955

The production for the first 24 hours was _____ barrels of fluid of which _____% was oil; _____% emulsion; _____% water; and _____% sediment. Gravity, °Bé. _____

If gas well _____, per 24 hours in _____ Gallons gasoline per 1,000 cu. ft. of gas _____

Rock pressure, lbs. per sq. in. _____

EMPLOYEES

Bob Mosser, Drilling Foreman, Driller _____, Driller _____

FORMATION RECORD

FROM—	TO—	TOTAL FEET	FORMATION
0	2093	2093	Surface
2093	2236	143	Sand - Ojo Alamo
2236	2870	634	Shale w/some sand - Kirtland
2870	3136	266	Interbedded shales, coals & sand - Fruitland
3136	3238	102	Sand - Fictured Cliffs
3238	4935	1697	Shale - Lewis
4935	5025	90	Sand - Cliff House
5025	5351	326	Interbedded sand, shales & coal - Menafee
5351	5351	0	Sand - Point Lookout.
5351	5490	39	Total Depth.

