

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER) Repair Well	X

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO**Farmington, New Mexico**
(Place)**March 24, 1964**
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

El Paso Natural Gas Company
(Company or Operator)**McElvain**Well No. **6-A** in **L**
(Unit)**NW** 1/4 **SW** 1/4 of Sec. **25**, T. **30N**, R. **7W**, NMPM, **Blanco Mesa Verde** Pool
(40-acre Subdivision)**Rio Arriba** County.FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Due to possible casing failure, bridge in open hole, this well will be repaired in the following manner:

If Tubing Can Be Pulled:


1. Pull tubing and set magnesium top drillable bridge plug at 5060'.
2. Pressure test 7" casing to 1500 PSI.
3. Run cement bond and corrosion inspection logs.
4. Drill out bridgeling and clean out open hole to 5670'.
5. Run full string of 4 1/2" casing and cement, bringing cement up into 7" casing.
6. Perforate and free Mesa Verde formation and complete

If Tubing Cannot Be Pulled:

1. Cut tubing off below 7" casing and pull.
2. Pressure test 7" casing to 1500 PSI.

Approved **APR 1 1964**, 19.....
Except as follows:Approved
OIL CONSERVATION COMMISSIONBy **Original Signed Emery C. Arnold**Title **Supervisor Dist. # 3****El Paso Natural Gas Company**
Company or OperatorBy **ORIGINAL SIGNED E. S. OBERLY**Position **Petroleum Engineer**

Send Communications regarding well to:

Name **E. S. Oberly**Address **Box 990, Farmington, New Mexico**

3. Set Baker Model "B" cement retainer at approximately 5060' and squeeze open hole.
4. Run cement bond and corrosion inspection logs on 7" casing.
5. Drill out retainer, set whipstock and drill to 5670'.
6. Complete as above.

STATE OF NEW MEXICO	
OIL CONSERVATION COMMISSION	
ALBUQUERQUE DISTRICT OFFICE	
NUMBER OF COPIES RECEIVED <u>2</u>	
DISTRICT	
SANTA FE	
FILE	
U.S.A.S.	
LAND OFFICE	
TRANSPORT	
OIL	
GAS	
PRODUCTION OFFICE	
OPERATOR	