


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 67966
Unit Northeast Flanco
Well Agreement No. 1,
Sec. 29



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<u>Subsequent Report of sand-water from I</u>

RECEIVED

APR 4 1951

U. S. GEOLOGICAL SURVEY
FARMINGTON, N.M.

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Notice

March 31, 1950

Well No. 6-29 is located 1770 ft. from N line and 1160 ft. from E line of sec. 29

Sec. 29
(1/4 Sec. and Sec. No.)

30N
(Twp.)

7W
(Range)

109W
(Meridian)

Flanco Mancosque
(Field)

San Juan
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 6700 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

On 3-12-50, perforated the Point Lookout zone thru 5 1/2" liner with 2 holes per foot 5120'-5140' & 5180'-5200'. Sand-water flood with 65000 gallons of water (including flush) and 50,000 lbs of sand. Injected 100 rubber balls in 5 stages during treatment. Maximum treating pressure 1300 PSI. Minimum treating pressure 500 PSI. Final pressure zero PSI. Average injection rate 46 barrels per minute.

Set Baker bridge plug at 5330' and perforated the Mancosque & Cliffhouse zones thru 5 1/2" liner with 2 holes per foot 5030'-5050', 5190'-5210', 5240'-5260', 5280'-5300', 5320'-5340' & 5316'-5336'. Sand-water flood with 65,000 gallons of water (including flush) & 50,000 lbs of sand. Injected 125 rubber balls in 8 stages during treatment. Maximum treating pressure 1300 PSI. Minimum treating pressure 525 PSI. Final pressure zero PSI. Average injection rate 51 barrels per minute.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company WAGGONER & NICHOLS COMPANY (UNIT OPERATOR)

Address P.O. Box 1237

Berango, Colorado

Original Signed
By DeLasso Loos DeLasso Loos

Title Field Superintendent

