

(SUBMIT IN TRIPLICATE)

Land Office Santa FeLease No. 079053Unit NortheastUNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYOil Agreement No. Sec. 929RECEIVED
JUN 20 1957
U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

SUNDRY NOTICES AND REPORTS ON WELLS

| | | |
|---|---|-------------------------------------|
| NOTICE OF INTENTION TO DRILL..... | SUBSEQUENT REPORT OF WATER SHUT-OFF..... | <input checked="" type="checkbox"/> |
| NOTICE OF INTENTION TO CHANGE PLANS..... | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... | |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF..... | SUBSEQUENT REPORT OF ALTERING CASING..... | |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR..... | |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE..... | SUBSEQUENT REPORT OF ABANDONMENT..... | |
| NOTICE OF INTENTION TO PULL OR ALTER CASING..... | SUPPLEMENTARY WELL HISTORY..... | |
| NOTICE OF INTENTION TO ABANDON WELL..... | | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 19, 1957

Well No. 34-19 is located 900 ft. from 1/4 line and 800 ft. from 1/4 line of sec. 19SE/4 Sec. 19
(1/4 Sec. and Sec. No.)30N
(Twp.)7E
(Range)RMPN
(Meridian)Blanco Mesavieja
(Field)Rio Arriba
(County or Subdivision)New Mexico
(State or Territory)The elevation of the derrick floor above sea level is 6375 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

On 5-4-57, ran 5 Jts 10-3/4" 32.75# E-40 casing - 158' set at 173'. Cemented with 200 sacks regular cement. Cement circulated. Tested casing with 800 PSI for 30 minutes. Held OK.

On 5-25-57, ran 115 Jts 7-5/8" 26.40# J-55 casing - 3533' set at 3545'. Cemented with 225 sacks 1:1 mixture of cement and pozzol with 1/2 gal and 1/2 lb. floccule per sack. Tested casing with 1000 PSI for 15 minutes. Held OK. Drilled with gas from 7-5/8" casing point.

On 6-1-57, ran 130 Jts 5-1/2" 15.50# J-55 casing - 5708' set at 5720'. Cemented with 150 sacks 1/2 gal cement with 1/2 lb. floccule per sack. Tested casing with 1000 PSI for 15 min. Held OK. Cement plug back depth 5690'. Top of cement at 3535', by temperature survey.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Blanchard & Nichols CompanyAddress P. O. Box 1237Durango, ColoradoBy DeLancey L. Loe DeLancey LoeTitle Field Superintendent

