

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R144.

5. LEASE DESIGNATION AND SERIAL NO.

SF 078740

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen, or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

7. UNIT AGREEMENT NAME

San Juan 30-5 Unit NP

8. FARM OR LEASE NAME

San Juan 30-5 Unit NP

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 19, T30N, R5W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

N.M.

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR
Northwest Pipeline Corporation

3. ADDRESS OF OPERATOR
P. O. Box 90 Farmington, N.M. 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface 660' FSL & 660' FWL

14. PERMIT NO. 15. ELEVATIONS (Show whether depth or etc.)
6286' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)
PULL OR ALTER CASING
MULTIPLE COMPLETION
ABANDON*
CHANGE PLANS

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)
REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

10-30-75

It is proposed to abandon this well in the following manner:

- (1) Run 2" tubing & spot 400' cement plug from 5412'-5012'
- (2) Spot 300' cement plug from 3051' to 2751'.
- (3) Spot 400' cement plug from 2560' to 2160'.
- (4) Spot 300' cement plug from 2000' to 1700'.
- (5) Spot 450' cement plug at surface.

A dry hole marker constructed of 4 1/2" pipe and extending 5' above ground level will be installed in the 8 5/8" casing.

The location will be cleaned and leveled when plugging operations are complete.

18. I hereby certify that the foregoing is true and correct

SIGNED D. H. Maroncelli
D. H. Maroncelli
(This space for Federal or State office use)


TITLE Petroleum Engineer

DATE 10-29-75

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE



NOV 9 1975

11/3/75
Copy to [unclear]

APPROVED
NOV 10, 1975
E. [unclear]
ACTING [unclear]

*See Instructions on Reverse Side

COPY TO ROSWELL
STAFF

10/30/75