

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator
BURLINGTON RESOURCES OIL & GAS COMPANY

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
960' FSL 1000' FWL, Sec. 22, T-30-N, R-7-W, NMPM

5. Lease Number
NM-013706

6. If Indian, All. or Tribe Name
Unit Agreement Name
San Juan 30-6 Unit


7. Well Name & Number
San Juan 30-6 U#73

8. API Well No.
30-039-07788

9. Field and Pool
Blanco Mesaverde

10. County and State
Rio Arriba Co, NM

11. County and State
Rio Arriba Co, NM



12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment

Type of Action

☐ Abandonment ☐ Change of Plans

☐ Recompletion ☐ New Construction

☐ Plugging Back ☐ Non-Routine Fracturing

☐ Casing Repair ☐ Water Shut off

☐ Altering Casing ☐ Conversion to Injection

☒ Other - tubing repair

13. Describe Proposed or Completed Operations

It is intended to repair the tubing on the subject well according to the attached procedure.

14. I hereby certify that the foregoing is true and correct.

Signed Ray Spahr (MH) Title Regulatory Administrator Date 7/22/98

TLW

(This space for Federal or State Office use)

APPROVED BY TS Duane W. Spencer Title _____ Date AUG 1 1998

CONDITION OF APPROVAL, if any:

NMOCD

San Juan 30-6 Unit # 73

Mesa Verde

960'S, 1000'W


Unit M, Section 22, T-30-N, R-07-W

Latitude / Longitude: 36° 47.60' / 107° 33.79'

DPNO: 69801

Tubing Repair Procedure

1. Hold safety meeting. Comply with all NMOCD, BLM and Burlington safety and environmental regulations. Test rig anchors and build blow pit prior to moving in rig. **Notify BROG Regulatory (Peggy Bradfield 326-9727) and the appropriate Regulatory Agency prior to pumping any cement job. If an unplanned cement job is required, approval is required before the job can be pumped. If verbal approval is obtained, document approval in DIMS/WIMS.** Allow as much time as possible prior to pump time in case the Agency decides to witness the cement job.
2. MOL and RU workover rig. Obtain and record all wellhead pressures. NU relief line. Blow well down and kill with 2% KCL water if necessary. NU BOP with stripping head. Test and record operation of BOP rams. Have wellhead and valves serviced as necessary. Test secondary seal and replace/install as necessary.
3. Mesa Verde, 2 3/8", 4.6#, J-55 tubing is set at 5859'. Release donut, pick up additional joints of tubing and tag bottom. (Record depth.) PBTD should be at +/- 5895'. TOOH with tubing. Visually inspect tubing for corrosion and replace any bad joints. Check tubing for scale build up and notify Operations Engineer.
4. TIH with 3 7/8" bit and bit sub on 2 3/8" tubing (contact Operations Engineer if casing scraper is needed) and round trip to below perforations, cleaning out with air/mist. **NOTE: When using air/mist, minimum mist rate is 12 bph.** If fill is encountered, and a casing scraper is being used, TOOH with casing scraper before cleaning out.
5. PU above the perforations and flow the well naturally, making short trips for clean up when necessary. TOOH with 2 3/8" tubing. TIH with one joint of 2 3/8" tubing with an expendable check on bottom and a seating nipple one joint off bottom then 1/2 of the 2 3/8" production tubing. Run a broach on sandline to insure that the tubing is clear. TIH with remaining 2 3/8" tubing and then broach this tubing. Replace any bad joints. CO to PBTD with air/mist.
6. Land tubing at 5859'. ND BOP and NU WH. Pump off expendable check. Connect to casing and circulate air to assure that expendable check has pumped off. Obtain pitot gauge up the tubing. If well will not flow on it's own, make swab run to SN. RD and MOL. Return well to production.

Recommended: 
Operations Engineer 7/16/98

Mike Haddenham
Office - (326-9577)
Home - (326-3102)
Pager - (327-8427)

Approved: 
Drilling Superintendent 7-17-98

Production Foreman – Bruce Voiles
Office - (326-9571)
Pager - (326-8842)