<u>District I</u> - (505) 393-6161 P. O. Box 1980 Hobbs, NM 88241-1980

District II - (505) 748-1283


811 S. First Artesia, NM 88210 District III - (505) 334-6178

1000 Rio Brazos Road

Aztec, NM 87410 District IV - (505) 827-7131

New Mexico Energy Minerals and Natural Resources Department

Oil Conservation Division 2040 South Pacheco Street Santa Fe, New Mexico 87505 (505) 827-7131



a sena ein.

1000 S

Form C-140 Revised 06/99

Submit Original Plus 2 Copies to appropriate District Office

APPLICATION FOR **WELL WORKOVER PROJECT**

Operator name and address Burlington Resources Oil and Gas						OGRID Number 014538					
			P.O. Bo	x 4289 Farmington	, NM 87499)					
Co	ntact Party	Peggy Co	ole					Phone	(50 5)	326-9700	
P	roperty Name					Well Nu	mber	API Numb	er		
SAN JUAN 30-6 UNIT				11		300390779300					
UL Section Township		Range Feet From The North/S		outh Line Fe		et From The	East/West Line		County		
	23	030N	006W	1450	FSL		990		FWL		RIO ARRIBA
	Workover	r									
D	ate Workover	Commenced 2/18/99		Previous Prod	ducing Poo	il(s) (Prior t	to Wor	kover)			
D	ate Workover	Completed 2/26/99		BLANCO MESA	AVERDE						
	Attach	a description	of the W	orkover Procedure	es performe	ed to incres	ase pro	oduction	_		
	State of	New Mexico		<u> </u>			·				
	County Pe 1. 1a 2. 1b 3. To	of San Juan eggy Cole, be arm the operat have made, o) ss.) ing first du or, or auth r caused to ny knowle	uly sworn, upon oath norized representativ to be made, a diliger dge, this application and accurate.	ve of the Op nt search of and the da	the product ta used to p	tion red prepare	cords reasona	ıbly ava	and/or tabl	e
_	County Pe 1. 1a 2. 1t 3. To	of San Juan eggy Cole, be am the operationave made, of the best of nor this Well are) ss.) ing first du or, or auth r caused t ny knowle complete	norized representation to be made, a diliger dge, this application and accurate.	ve of the Op nt search of and the da	the product	tion red prepare	cords reasona	ıbly ava	and/or tabl	e
٠	County	of San Juan eggy Cole, be am the operationave made, of the best of nor this Well are) ss.) ing first du or, or auth r caused t ny knowle complete	norized representation to be made, a diliger dge, this application and accurate.	ve of the Op nt search of and the da	the product ta used to p	tion red prepare	cords reasona	ıbly ava	and/or tabl	
SUE	County Pe 1. 1a 2. 1t 3. To	of San Juan eggy Cole, be am the operat have made, o the best of n r this Well are) ss.) ing first du or, or auth r caused t ny knowle complete D before n	norized representation to be made, a diliger dge, this application and accurate.	ve of the Op nt search of and the da	the product ta used to p	tion red prepare	cords reasona	on curve	and/or tabl	e
SUE	County Pe 1. 1a 2. 11 3. To for	of San Juan eggy Cole, be am the operat nave made, o the best of n r this Well are D SWORN TO) ss.) ing first du or, or auti r caused t ny knowle complete D before n	norized representation be made, a diliger dge, this application and accurate. All day of	ve of the Op nt search of and the da	the product ta used to p	tion red prepare	cords reasona the production	on curve	and/or tabl	e
My OR	County Pe 1. 1a 2. 11 3. To nature BSCRIBED AND Commission exp OIL CONSERV CERTIFICATIO	of San Juan eggy Cole, be am the operat nave made, o the best of n this Well are D SWORN TO pires:) ss.) ing first du or, or auti r caused t ny knowle complete D before n	norized representative be made, a diliger dge, this application and accurate. The this day of	ve of the Op nt search of and the da	the product ta used to p	tion recorded	cords reasona the production the production	on curve	and/or tabl	• <u>/z - 4 - 5</u> allega
My OR	County Pe 1. 1a 2. 11 3. To nature BSCRIBED AND Commission exp OIL CONSERV CERTIFICATIO This Applicathe data sh	of San Juan eggy Cole, be am the operat have made, o the best of n this Well are D SWORN TO pires: ON OFAPPRO ontion is hereby ows positive) ss.) ing first duor, or autir caused to the complete c	norized representation be made, a diliger dge, this application and accurate. The this day of Control day of C	ve of the Opnt search of and the da	the product ta used to p Reg. Admins) f dis designate Division not	ed a Weifies th	Notary F	curve	and/or table Date	sion hereby verifie
SUE My OR	County Pe 1. 1a 2. 11 3. To nature BSCRIBED AND Commission exp OIL CONSERV CERTIFICATIO This Applicathe data sh	of San Juan eggy Cole, be am the operat have made, o the best of n this Well are D SWORN TO pires: ON OFAPPRO ontion is hereby ows positive) ss.) ing first duor, or autir caused to the complete c	norized representative be made, a diliger dge, this application and accurate. The this day of the control of t	ve of the Opnt search of and the da	the product ta used to p Reg. Admins) f dis designate Division not	ed a Weifies th	Notary F	curve	and/or table Date	sion hereby verifie

	בי ווהוו ככ	5	Lease Number
		ر مرد درجی ا	SF-078741
1. Type of Well	- 070 Erdini	(83)	If Indian, All. or
GAS			Tribe Name
		7.	Unit Agreement Name
2. Name of Operator		-	
-			
RESOURCES OIL & GAS COMPANY			San Juan 30-6 Unit
		8.	
3. Address & Phone No. of Operator			San Juan 30-6 U #11
PO Box 4289, Farmington, NM 87499 (505) 326-9700		9.	API Well No.
		• •	30-039-07793
4. Location of Well, Footage, Sec., T, R, M 1450'FSL, 990'FWL, Sec.23, T-30-N, R-6-W, NMPM.		10.	Field and Pool Blanco Mesaverde
1450' FSL, 990' FWL, Sec.25, 1-30-N, R-0-W, NMFM-		11	County and State
			Rio Arriba Co, NM
12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,		THER	DATA
Type of Submission Type of Act Notice of Intent Abandonment	:1 0n Change o	£ D1-	
Recompletion	New Cons	+ *110+	ion
X Subsequent Report Plugging Back	Non-Rout	ine F	racturing
Casing Repair	Water Sh	ut of	f
X Subsequent Report Plugging Back Casing Repair Altering Casing	_ Conversi	on to	Injection
X Other - Pay add			
13. Describe Proposed or Completed Operations			
13. Describe laspecte of temperature specialists			
2-18-99 MIRU. TOOH w/2 3/8" tbg. Left slick line			
set CIBP @ 5190'. PT CIBP to 1000 psi, 1000 psi, OK. TOOH w/pkr. TIH, ran CBL 4380'. SDON.			
1000 psi, OK. TOOH w/pkr. TIH, ran CBL 4380'. SDON. 2-19-99 TIH w/7 5/8" pkr. PT lnr top to 1000 psi OK. ND WH. Weld stub on csg. Install 7' psi, OK. NU BOP. SDON.	@ 3800-51 L, OK. PT 7 " tbg hang	90', '5/8' er. P	TOC on 5 ½" Înr @ ' csg to 1200 psi, T tbg hanger to 1200
1000 psi, OK. TOOH w/pkr. TIH, ran CBL 4380'. SDON. 2-19-99 TIH w/7 5/8" pkr. PT lnr top to 1000 psi OK. ND WH. Weld stub on csg. Install 7	@ 3800-51 L, OK. PT 7 " tbg hang 45, 4550, 4 25, 4935, holes tota	90', 5/8" er. P 780, 4945, 1. Ac	TOC on 5 ½" Inr @ ' csg to 1200 psi, T tbg hanger to 1200 4790, 4800, 4810, 4950, 5015, 5020, idize w/10% acetic
1000 psi, OK. TOOH w/pkr. TIH, ran CBL 4380'. SDON. 2-19-99 TIH w/7 5/8" pkr. PT lnr top to 1000 psi OK. ND WH. Weld stub on csg. Install 7' psi, OK. NU BOP. SDON. 2-20-99 Perf Lewis @ 4525, 4530, 4535, 4540, 454 4820, 4845, 4850, 4855, 4865, 4915, 49: 5030, 5040, 5050' w/25 0.29" diameter acid. Frac Lewis w/896 bbl 25# linear after frac.	@ 3800-51 L, OK. PT 7 " tbg hang 45, 4550, 4 25, 4935, holes tota	90', 5/8" er. P 780, 4945, 1. Ac	TOC on 5 ½" Inr @ ' csg to 1200 psi, T tbg hanger to 1200 4790, 4800, 4810, 4950, 5015, 5020, idize w/10% acetic
1000 psi, OK. TOOH w/pkr. TIH, ran CBL 4380'. SDON. 2-19-99 TIH w/7 5/8" pkr. PT lnr top to 1000 psi OK. ND WH. Weld stub on csg. Install 7' psi, OK. NU BOP. SDON. 2-20-99 Perf Lewis @ 4525, 4530, 4535, 4540, 454 4820, 4845, 4850, 4855, 4865, 4915, 49: 5030, 5040, 5050' w/25 0.29" diameter acid. Frac Lewis w/896 bbl 25# linear after frac. 2-21-99 Blow well & CO.	@ 3800-51 i, OK. PT 7 " tbg hang 45, 4550, 4 25, 4935, holes tota gel, 200,0	90', 5/8' er. P :780, 4945, 1. Ac	TOC on 5 ½" Inr @ ' csg to 1200 psi, T tbg hanger to 1200 4790, 4800, 4810, 4950, 5015, 5020, idize w/10% acetic 0/40 Brady sd. CO
1000 psi, OK. TOOH w/pkr. TIH, ran CBL 4380'. SDON. 2-19-99 TIH w/7 5/8" pkr. PT lnr top to 1000 psi OK. ND WH. Weld stub on csg. Install 7' psi, OK. NU BOP. SDON. 2-20-99 Perf Lewis @ 4525, 4530, 4535, 4540, 454 4820, 4845, 4850, 4855, 4865, 4915, 49: 5030, 5040, 5050' w/25 0.29" diameter acid. Frac Lewis w/896 bbl 25# linear after frac. 2-21-99 Blow well & CO. TOOH w/pkr. TIH w/4 34" m	@ 3800-51 i, OK. PT 7 " tbg hang 45, 4550, 4 25, 4935, holes tota gel, 200,0	90', 5/8' er. P :780, 4945, 1. Ac	TOC on 5 ½" Inr @ ' csg to 1200 psi, T tbg hanger to 1200 4790, 4800, 4810, 4950, 5015, 5020, idize w/10% acetic 0/40 Brady sd. CO
1000 psi, OK. TOOH w/pkr. TIH, ran CBL 4380'. SDON. 2-19-99 TIH w/7 5/8" pkr. PT lnr top to 1000 psi OK. ND WH. Weld stub on csg. Install 7' psi, OK. NU BOP. SDON. 2-20-99 Perf Lewis @ 4525, 4530, 4535, 4540, 454 4820, 4845, 4850, 4855, 4865, 4915, 495 5030, 5040, 5050' w/25 0.29" diameter acid. Frac Lewis w/896 bbl 25# linear after frac. 2-21-99 Blow well & CO. 2-22-99 Blow well & CO. TOOH w/pkr. TIH w/4 34" m 2-23-99 Blow well & CO to CIBP @ 5190'.	@ 3800-51 i, OK. PT 7 " tbg hang 45, 4550, 4 25, 4935, holes tota gel, 200,0	90', 5/8' er. P 780, 4945, 1. Ac 00# 2	TOC on 5 ½" Inr @ csg to 1200 psi, T tbg hanger to 1200 4790, 4800, 4810, 4950, 5015, 5020, idize w/10% acetic 0/40 Brady sd. CO & CO.
1000 psi, OK. TOOH w/pkr. TIH, ran CBL 4380'. SDON. 2-19-99 TIH w/7 5/8" pkr. PT lnr top to 1000 psi OK. ND WH. Weld stub on csg. Install 7' psi, OK. NU BOP. SDON. 2-20-99 Perf Lewis @ 4525, 4530, 4535, 4540, 454 4820, 4845, 4850, 4855, 4865, 4915, 49: 5030, 5040, 5050' w/25 0.29" diameter acid. Frac Lewis w/896 bbl 25# linear after frac. 2-21-99 Blow well & CO. TOOH w/pkr. TIH w/4 34" m	@ 3800-51 i, OK. PT 7 " tbg hang 45, 4550, 4 25, 4935, holes tota gel, 200,0	90', 5/8' er. P 780, 4945, 1. Ac 00# 2	TOC on 5 ½" Inr @ csg to 1200 psi, T tbg hanger to 1200 4790, 4800, 4810, 4950, 5015, 5020, idize w/10% acetic 0/40 Brady sd. CO & CO.
1000 psi, OK. TOOH w/pkr. TIH, ran CBL 4380'. SDON. 2-19-99 TIH w/7 5/8" pkr. PT lnr top to 1000 psi OK. ND WH. Weld stub on csg. Install 7' psi, OK. NU BOP. SDON. 2-20-99 Perf Lewis @ 4525, 4530, 4535, 4540, 454 4820, 4845, 4850, 4855, 4865, 4915, 49: 5030, 5040, 5050' w/25 0.29" diameter acid. Frac Lewis w/896 bbl 25# linear after frac. 2-21-99 Blow well & CO. 2-22-99 Blow well & CO. TOOH w/pkr. TIH w/4 %" m 2-23-99 Blow well & CO to CIBP @ 5190'. 2-24-99 Blow well & CO. Mill out CIBP @ 5190'. To 2-25-99 Blow well & CO. TOOH. 2-26-99 TIH w/192 jts 2 3/8" 4.7# J-55 EUE tbg,	@ 3800-51 i, OK. PT 7 " tbg hang 45, 4550, 4 25, 4935, holes tota gel, 200,0 mill. Blow	90', 5/8' er. P 780, 4945, 1. Ac 00# 2 well 0 @ 63	TOC on 5 ½" Inr @ ' csg to 1200 psi, T tbg hanger to 1200 4790, 4800, 4810, 4950, 5015, 5020, idize w/10% acetic 0/40 Brady sd. CO & CO. 105'. Blow well & CO
1000 psi, OK. TOOH w/pkr. TIH, ran CBL 4380'. SDON. 2-19-99 TIH w/7 5/8" pkr. PT lnr top to 1000 psi OK. ND WH. Weld stub on csg. Install 7' psi, OK. NU BOP. SDON. 2-20-99 Perf Lewis @ 4525, 4530, 4535, 4540, 4544 4820, 4845, 4850, 4855, 4865, 4915, 49: 5030, 5040, 5050' w/25 0.29" diameter acid. Frac Lewis w/896 bbl 25# linear after frac. 2-21-99 Blow well & CO. 2-22-99 Blow well & CO. TOOH w/pkr. TIH w/4 %" m 2-23-99 Blow well & CO to CIBP @ 5190'. 2-24-99 Blow well & CO. Mill out CIBP @ 5190'. T 2-25-99 Blow well & CO. TOOH.	@ 3800-51 i, OK. PT 7 " tbg hang 45, 4550, 4 25, 4935, holes tota gel, 200,0 mill. Blow	90', 5/8' er. P 780, 4945, 1. Ac 00# 2 well 0 @ 63	TOC on 5 ½" Inr @ or csg to 1200 psi, T tbg hanger to 1200 4790, 4800, 4810, 4950, 5015, 5020, idize w/10% acetic 0/40 Brady sd. CO & CO. 105'. Blow well & CO
1000 psi, OK. TOOH w/pkr. TIH, ran CBL 4380'. SDON. 2-19-99 TIH w/7 5/8" pkr. PT lnr top to 1000 psi OK. ND WH. Weld stub on csg. Install 7' psi, OK. NU BOP. SDON. 2-20-99 Perf Lewis @ 4525, 4530, 4535, 4540, 4544 4820, 4845, 4850, 4855, 4865, 4915, 4955030, 5040, 5050' w/25 0.29" diameter acid. Frac Lewis w/896 bbl 25# linear after frac. 2-21-99 Blow well & CO. 2-22-99 Blow well & CO. TOOH w/pkr. TIH w/4 34" meleased. 2-24-99 Blow well & CO. Mill out CIBP @ 5190'. Teleased. 2-26-99 TIH w/192 jts 2 3/8" 4.7# J-55 EUE tbg, Rig released.	@ 3800-51 i, OK. PT 7 " tbg hang 45, 4550, 4 25, 4935, holes tota gel, 200,0 mill. Blow FIH to PBTI landed @ 6	90', 5/8' er. P 780, 4945, 1. Ac 00# 2 well 0 @ 63	TOC on 5 ½" Inr @ or csg to 1200 psi, T tbg hanger to 1200 4790, 4800, 4810, 4950, 5015, 5020, idize w/10% acetic 0/40 Brady sd. CO & CO. 105'. Blow well & CO
1000 psi, OK. TOOH w/pkr. TIH, ran CBL 4380'. SDON. 2-19-99 TIH w/7 5/8" pkr. PT lnr top to 1000 psi OK. ND WH. Weld stub on csg. Install 7 psi, OK. NU BOP. SDON. 2-20-99 Perf Lewis @ 4525, 4530, 4535, 4540, 454 4820, 4845, 4850, 4855, 4865, 4915, 495 5030, 5040, 5050' w/25 0.29" diameter acid. Frac Lewis w/896 bbl 25# linear after frac. 2-21-99 Blow well & CO. 2-22-99 Blow well & CO. TOOH w/pkr. TIH w/4 3" m 2-23-99 Blow well & CO to CIBP @ 5190'. 2-24-99 Blow well & CO. Mill out CIBP @ 5190'. T 2-25-99 Blow well & CO. TOOH. 2-26-99 TIH w/192 jts 2 3/8" 4.7# J-55 EUE tbg, Rig released.	@ 3800-51 i, OK. PT 7 " tbg hang 45, 4550, 4 25, 4935, holes tota gel, 200,0 mill. Blow FIH to PBTI landed @ 6	90', 5/8' er. P 780, 4945, 1. Ac 00# 2 well 0 @ 63	TOC on 5 ½" Inr @ 'csg to 1200 psi, T tbg hanger to 1200 4790, 4800, 4810, 4950, 5015, 5020, idize w/10% acetic 0/40 Brady sd. CO & CO. 105'. Blow well & CO . ND BOP. NU WH. RD.
1000 psi, OK. TOOH w/pkr. TIH, ran CBL 4380'. SDON. 2-19-99 TIH w/7 5/8" pkr. PT lnr top to 1000 psi OK. ND WH. Weld stub on csg. Install 7 psi, OK. NU BOP. SDON. 2-20-99 Perf Lewis @ 4525, 4530, 4535, 4540, 4544 4820, 4845, 4850, 4855, 4865, 4915, 495030, 5040, 5050' w/25 0.29" diameter acid. Frac Lewis w/896 bbl 25# linear after frac. 2-21-99 Blow well & CO. 2-22-99 Blow well & CO. TOOH w/pkr. TIH w/4 34" m2-23-99 Blow well & CO to CIBP @ 5190'. 2-24-99 Blow well & CO. Mill out CIBP @ 5190'. T2-25-99 Blow well & CO. TOOH. 2-26-99 TIH w/192 jts 2 3/8" 4.7# J-55 EUE tbg, Rig released. 14. I hereby certify that the foregoing is true and content of the structure of the struct	@ 3800-51 i, OK. PT 7 " tbg hang 45, 4550, 4 25, 4935, holes tota gel, 200,0 mill. Blow FIH to PBTI landed @ 6	90', 5/8' er. P 780, 4945, 1. Ac 00# 2 well 0 @ 63	TOC on 5 ½" Inr @ 'csg to 1200 psi, T tbg hanger to 1200 4790, 4800, 4810, 4950, 5015, 5020, idize w/10% acetic 0/40 Brady sd. CO & CO. 105'. Blow well & CO . ND BOP. NU WH. RD.
1000 psi, OK. TOOH w/pkr. TIH, ran CBL 4380'. SDON. 2-19-99 TIH w/7 5/8" pkr. PT lnr top to 1000 psi OK. ND WH. Weld stub on csg. Install 7' psi, OK. NU BOP. SDON. 2-20-99 Perf Lewis @ 4525, 4530, 4535, 4540, 4544 4820, 4845, 4850, 4855, 4865, 4915, 4955030, 5040, 5050' w/25 0.29" diameter acid. Frac Lewis w/896 bbl 25# linear after frac. 2-21-99 Blow well & CO. 2-22-99 Blow well & CO. TOOH w/pkr. TIH w/4 %" m 2-23-99 Blow well & CO. TOOH w/pkr. TIH w/4 %" m 2-23-99 Blow well & CO. Mill out CIBP @ 5190'. 2-24-99 Blow well & CO. Mill out CIBP @ 5190'. To 2-25-99 Blow well & CO. TOOH. 2-26-99 TIH w/192 jts 2 3/8" 4.7# J-55 EUE tbg, Rig released. 14. I hereby certify that the foregoing is true and continued the specific continued to	@ 3800-51 L, OK. PT 7 " tbg hang 45, 4550, 4 25, 4935, holes tota gel, 200,0 mill. Blow FIH to PBTF landed @ @ correct. ministrator	90', 5/8'er. P 780, 4945, 1. Ac 00# 2 well 0 @ 65	Con 5 % inr 6 Con 5 % inr 6 Con 5 % inr 6 Con 1200 psi, T tbg hanger to 1200 4790, 4800, 4810, 4950, 5015, 5020, idize w/10% acetic 0/40 Brady sd. CO & CO. 105'. Blow well & CO ND BOP. NU WH. RD.
1000 psi, OK. TOOH w/pkr. TIH, ran CBL 4380'. SDON. 2-19-99 TIH w/7 5/8" pkr. PT lnr top to 1000 psi OK. ND WH. Weld stub on csg. Install 7 psi, OK. NU BOP. SDON. 2-20-99 Perf Lewis @ 4525, 4530, 4535, 4540, 454 4820, 4845, 4850, 4855, 4865, 4915, 49: 5030, 5040, 5050' w/25 0.29" diameter acid. Frac Lewis w/896 bbl 25# linear after frac. 2-21-99 Blow well & CO. 2-22-99 Blow well & CO. TOOH w/pkr. TIH w/4 %" m 2-23-99 Blow well & CO to CIBP @ 5190'. Telested Section 2-24-99 Blow well & CO. Mill out CIBP @ 5190'. Telested Section 2-26-99 TIH w/192 jts 2 3/8" 4.7# J-55 EUE tbg, Rig released. 14. I hereby certify that the foregoing is true and continuous continuous for the section of the section 2 displayed for Federal or State Office use) APPROVED BY Title	@ 3800-51 i, OK. PT 7 " tbg hang 45, 4550, 4 25, 4935, holes tota gel, 200,0 mill. Blow FIH to PBTI landed @ 6	90', 5/8'er. P 780, 4945, 1. Ac 00# 2 well 0 @ 65	TOC on 5 ½" Inr @ 'csg to 1200 psi, T tbg hanger to 1200 4790, 4800, 4810, 4950, 5015, 5020, idize w/10% acetic 0/40 Brady sd. CO & CO. 105'. Blow well & CO . ND BOP. NU WH. RD.
1000 psi, OK. TOOH w/pkr. TIH, ran CBL 4380'. SDON. 2-19-99 TIH w/7 5/8" pkr. PT lnr top to 1000 psi OK. ND WH. Weld stub on csg. Install 7 psi, OK. NU BOP. SDON. 2-20-99 Perf Lewis @ 4525, 4530, 4535, 4540, 454 4820, 4845, 4850, 4855, 4865, 4915, 49: 5030, 5040, 5050' w/25 0.29" diameter acid. Frac Lewis w/896 bbl 25# linear after frac. 2-21-99 Blow well & CO. 2-22-99 Blow well & CO. TOOH w/pkr. TIH w/4 %" m 2-23-99 Blow well & CO. TOOH w/pkr. TIH w/4 %" m 2-23-99 Blow well & CO. Mill out CIBP @ 5190'. To 2-25-99 Blow well & CO. Mill out CIBP @ 5190'. To 2-25-99 Blow well & CO. TOOH. 2-26-99 TIH w/192 jts 2 3/8" 4.7# J-55 EUE tbg, Rig released. 14. I hereby certify that the foregoing is true and continued for the con	@ 3800-51 L, OK. PT 7 " tbg hang 15, 4550, 4 25, 4935, holes tota gel, 200,0 mill. Blow FIH to PBTF landed @ @ correct. ministrator	90', 5/8'er. P 780, 4945, 1. Ac 00# 2 well 0 @ 65	Con 5 % inr 6 Cosg to 1200 psi, T tbg hanger to 1200 4790, 4800, 4810, 4950, 5015, 5020, idize w/10% acetic 0/40 Brady sd. CO & CO. 105'. Blow well & CO ND BOP. NU WH. RD. PIED FOR RECORD MAR 1 0 1999
1000 psi, OK. TOOH w/pkr. TIH, ran CBL 4380'. SDON. 2-19-99 TIH w/7 5/8" pkr. PT lnr top to 1000 psi OK. ND WH. Weld stub on csg. Install 7 psi, OK. NU BOP. SDON. 2-20-99 Perf Lewis @ 4525, 4530, 4535, 4540, 454 4820, 4845, 4850, 4855, 4865, 4915, 49: 5030, 5040, 5050' w/25 0.29" diameter acid. Frac Lewis w/896 bbl 25# linear after frac. 2-21-99 Blow well & CO. 2-22-99 Blow well & CO. TOOH w/pkr. TIH w/4 %" m 2-23-99 Blow well & CO. TOOH w/pkr. TIH w/4 %" m 2-23-99 Blow well & CO. Mill out CIBP @ 5190'. To 2-25-99 Blow well & CO. Mill out CIBP @ 5190'. To 2-25-99 Blow well & CO. TOOH. 2-26-99 TIH w/192 jts 2 3/8" 4.7# J-55 EUE tbg, Rig released. 14. I hereby certify that the foregoing is true and continued for the con	@ 3800-51 L, OK. PT 7 " tbg hang 15, 4550, 4 25, 4935, holes tota gel, 200,0 mill. Blow FIH to PBTF landed @ @ correct. ministrator	90', 5/8'er. P 780, 4945, 1. Ac 00# 2 well 0 @ 65	Con 5 % inr @ csg to 1200 psi, T tbg hanger to 1200 4790, 4800, 4810, 4950, 5015, 5020, idize w/10% acetic 0/40 Brady sd. CO & CO. 105'. Blow well & CO ND BOP. NU WH. RD. PIED FOR RECORD MAR 1 0 1999
1000 psi, OK. TOOH w/pkr. TIH, ran CBL 4380'. SDON. 2-19-99 TIH w/7 5/8" pkr. PT lnr top to 1000 psi OK. ND WH. Weld stub on csg. Install 7 psi, OK. NU BOP. SDON. 2-20-99 Perf Lewis @ 4525, 4530, 4535, 4540, 454 4820, 4845, 4850, 4855, 4865, 4915, 49: 5030, 5040, 5050' w/25 0.29" diameter acid. Frac Lewis w/896 bbl 25# linear after frac. 2-21-99 Blow well & CO. 2-22-99 Blow well & CO. TOOH w/pkr. TIH w/4 %" m 2-23-99 Blow well & CO to CIBP @ 5190'. Telested Section 2-24-99 Blow well & CO. Mill out CIBP @ 5190'. Telested Section 2-26-99 TIH w/192 jts 2 3/8" 4.7# J-55 EUE tbg, Rig released. 14. I hereby certify that the foregoing is true and continuous continuous for the section of the section 2 displayed for Federal or State Office use) APPROVED BY Title	@ 3800-51 L, OK. PT 7 " tbg hang 15, 4550, 4 25, 4935, holes tota gel, 200,0 mill. Blow FIH to PBTF landed @ @ correct. ministrator	90', 5/8'er. P 780, 4945, 1. Ac 00# 2 well 0 @ 65	Con 5 % inr @ csg to 1200 psi, T tbg hanger to 1200 4790, 4800, 4810, 4950, 5015, 5020, idize w/10% acetic 0/40 Brady sd. CO & CO. 105'. Blow well & CO ND BOP. NU WH. RD. PIED FOR RECORD MAR 1 0 1999

OPERATOR

"I hereby certify that the rules of the Oil Conservation Division have been complied with and that the information given above is true and complete to the best of my knowledge and belief.

OIL CONSERVATION DIVISION

HB Pull 12/3/99

COMP NAME TO	W_ID USER	DISP_MO	GRS GAS PR
SAN JUAN 30-6 UNIT 11 697	3601 69736	11/30/98	1149.32
SAN JUAN 30-6 UNIT 11 697	3601 69736	12/31/98	1775.76
SAN JUAN 30-6 UNIT 11 697	3601 69736	1/31/99	2555.75
SAN JUAN 30-6 UNIT 11 697	3601 69736	2/28/99	890.115
SAN JUAN 30-6 UNIT 11 697	3601 69736	3/31/99	12623.457
SAN JUAN 30-6 UNIT 11 697	3601 69736	4/30/99	11764.71
SAN JUAN 30-6 UNIT 11 697	3601 69736	5/31/99	10566.32
SAN JUAN 30-6 UNIT 11 697	3601 69736	6/30/99	8810.87
SAN JUAN 30-6 UNIT 11 697	3601 69736	7/31/99	9113.42
SAN JUAN 30-6 UNIT 11 697	3601 69736	8/31/99	8238.94
SAN JUAN 30-6 UNIT 11 697	3601 69736	9/30/99	7314.99
SAN JUAN 30-6 UNIT 11 697	3601 69736	10/31/99	8303.64

MA.	DP NO	PRODN	DISP	Volume
11	69736	199711	00	1097.0228
11	69736	199712	00	706.83956
11	69736	199801	00	765.66116
11	69736	199802	00	577.43204
11	69736	199803	00	1455.8346
11	69736	199804	00	1749.9426
11	69736	199805	00	1444.0703
11	69736	199806	00	1131.3354
11	69736	199807	00	1329.3682
11	69736	199808	00	1544.067
11	69736	199809	00	2462.6643
11	69736	199810	00	2368.5498