



5 - U.S.G.S.

1 - W. R. Johnston

1 - File

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa FeLease No. 87 878740Unit 10-3# 14-08-001-346

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	X
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 9, 1956

Well No. 14-19 is located 1675 ft. from [N] line and 800 ft. from [E] line of sec. 19SE 1/4 Sec. 19
(1/4 Sec. and Sec. No.)30N 9W
(Twp.)

(Range)

N.M.P.M.
(Meridian)Elanco - New Mexico
(Field)Elko Apache
(County or Subdivision)New Mexico
(State or Territory)The elevation of the ~~original~~ Spudded Ground above sea level is 6424 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded with spudder at 4:00 P.M. 3-24-56. Drilled to 156', set 134.6' of 9 5/8" O.D., 32.2W, N-40 casing, with Jones Pattern shoe, at 183' (Ord.) and cemented with 15C sand regular cement. P.O.B. at 9:30 P.M. 3-26-56. Released spudder. Moved on Rotary Rig. W.O.C. for 24 hours; casing tested O.K. Drilled ahead.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pacific Northwest Pipeline CorporationAddress 413 1/2 West MainFarmingtonNew MexicoBy Original signed by T. A. DuganTitle District Engineer

