

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		7. UNIT AGREEMENT NAME Northeast Blanco Unit
2. NAME OF OPERATOR Blackwood & Nichols Company		8. FARM OR LEASE NAME Agrmt. No. 1, Sec. 929
3. ADDRESS OF OPERATOR P.O. Box 1237 Durango, Colorado 81301		9. WELL NO. 24
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface  420' F/SL - 2515' F/EL		10. FIELD AND POOL, OR WILDCAT Blanco Mesaverde
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 17-30N-7W NMPM
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6282' GL		12. COUNTY OR PARISH Rio Arriba
		13. STATE New Mexico


16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF <input type="checkbox"/>	PULL OR ALTER CASING <input type="checkbox"/>	WATER SHUT-OFF <input type="checkbox"/>	REPAIRING WELL <input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	MULTIPLE COMPLETE <input type="checkbox"/>	FRACTURE TREATMENT <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	ABANDON* <input type="checkbox"/>	SHOOTING OR ACIDIZING <input type="checkbox"/>	ABANDONMENT* <input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	(Other) <input type="checkbox"/>	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

On 2-25-76, spotted 250 gals., 15% HCl, perforated Point Lookout Zone 5420' - 5520' with one per foot Glass Jets. Sand-water fractured with 76,000 gals water, 67,000 lbs 20 - 40 sand, with 2½ lbs FR-2X per 1000 gals water and 1400 lbs Westblock 3X. Maximum pressure 1800 PSI, minimum 1000 PSI, average 1200 PSI, injection rate 55 bbls/min. Set retrievable bridge plug at 5157', perforated Cliffhouse Zone 5050' - 5100', two Glass Jets per foot. Sand-water fractured with 54,600 gals water, 44,000 lbs 20 - 40 sand, 2½#, FR-2X per 1000 gals water. Maximum pressure 1675 PSI, minimum pressure 1200 PSI, average 1500 PSI, injection rate 43 bbls/min.



MAR 3 1976  
U. S. GEOLOGICAL SURVEY  
DENVER, COLO.

18. I hereby certify that the foregoing is true and correct

SIGNED Delasso Loos TITLE District Manager

DATE 3-2-76

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_

DATE \_\_\_\_\_