

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

ENERGEN RESOURCES CORPORATION

3. Address and Telephone No.

2198 Bloomfield Highway, Farmington, NM 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

990' FSL, 1750' FWL, Sec. 18, T30N, R4W, N.M.P.M.

N

5. Lease Designation and Serial No.

SF-079485A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA. Agreement Designation

San Juan 30-4 Unit

8. Well Name and No.

San Juan 30-4 Unit 1

9. API Well No.

30-039-07840

10. Field and Pool, or exploratory Area

E. Blanco PC

11. County or Parish, State

Rio Arriba County NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Deepen & Case
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5/27/99 MIRU. TOH w/ tubing.

5/28/99 TIH w/ 6 1/8" bit on 2 7/8" workstring. Tag tight spot at 4107'. Tried to work bit through casing. Could not.

6/1/99 TOH with bit. TIH with 6 1/8 taper mill.

6/2/99 Tag tight spot @ 4107'. Mill from 4107'-4110'. Mill quit. TOH.

6/3/99 TIH with taper mill. Mill from 4110'-4115'. Fell through. TIH and clean out to 4154'. TOH.

6/4/99 TIH with 6 1/8" bit. Drill to 4280' w/ air mist.

6/5/99 Drill to 4464'. Circ. hole clean. POH.

6/6/99 Drill to 4520'. Load hole with water. TOH.

6/7/99 Ran 102 jts. 4 1/2" 10.5# J-55 ST&C casing set at 4505'. Cemented w/ 235 sx 3% econolite, 6#/sk gilsonite, 1/4#/sk flocele followed by 125 sx Class B. 4% gel 6#/sk gilsonite, 1/4#/sk flocele and 1% CaCL2. (877 cu. ft.) Plug down 6 pm 6/7/99. Circ. 40 sx to surface. W. O. Completion.

JUL 2 1999

14. I hereby certify that the foregoing is true and correct

Signed

Monica Taylor

Title Production Assistant

Date 6/18/99

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

JUL 26 1999

FARMINGTON FIELD OFFICE