

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office New Mexico
Lease No. 03385
Unit W 1/4 Sec. 17

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Amarillo, Texas, October 6, 1952Well No. McPherson
1-Federalis located 1850 ft. from 1/4 line and 1190 ft. from 1/2 line of sec. _____Sec. 17 R-30-N. 1-6-E 11-11-N
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)Gomez Ranch anticline Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the ground ~~derrick floor~~ above sea level is 5647 ft.
The South 1/2 of Section 17-30-6 is designated as the drilling unit
for this well.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

This well will start in the Wasatch formation and will be drilled to a depth of 6000' into the Mancos shale. Rotary tools will be used to the top of the Cliff House formation expected at a depth of 5300', at which point a string of 5 1/2" 15.50# J-55 casing will be set and cemented with 150 sacks of cement. 100 feet of 9 5/8" 36.00# X-40 casing will be set and cemented with sufficient cement to fill the annular space back of the casing to the bottom of the cellar. The Pictured Cliff and Point Lookout formations are expected at depths of 3425' and 5640' respectively. The well is to be drilled in with gas. After drilling in the well is to be shot with 1500-2000 quarts of nitroglycerin and, after cleaning out after shooting, 6000' of 2" 4.00# X-80 tubing will be run to bottom. Drilling is to start immediately after the casing and tubing allotment is received from the PAG.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Westpan Hydrocarbon CompanyAddress 418 Polk StreetAmarillo, TexasBy E. C. McGreeTitle President