

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
BLM

Sundry Notices and Reports on Wells

99 JUN 16 PM 2:00

1. Type of Well
GAS

RECEIVED
JUN 23 1995

2. Name of Operator

MERIDIAN OIL OIL CON. DIV.
DIST. 3

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1850' FSL, 1650' FWL, Sec. 14, T-30-N, R-7-W, NMPM

5. Lease Number
NM-012573

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

San Juan 30-6 Unit

8. Well Name & Number

San Juan 30-6 U #66

9. API Well No.

30-039-07844

10. Field and Pool

Wildcat; Navajo City PC

11. County and State

Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent

☒ Abandonment

☐ Change of Plans

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

☐ Other -

13. Describe Proposed or Completed Operations

6-6-95 MIRU. ND WH. NU BOP. TIH, could not release pkr 2996'. SDON. (Verbal approval to change plans from Steve Mason, BLM.)

6-7-95 Plug #1: pump 50 sx Class "B" cmt down tbg @3004-3203'. Displaced to 2900' down tbg. WOC. PT tbg & cmt plug to 1000 psi/10 min, OK. TIH w/gauge ring, TOC @ 2737'. TOOH. TIH w/1 13/16" tbg cutter, jet cut 2 3/8" tbg off @ 2710'. Plug #2: pump 26 sx Class "B" cmt inside csg @ 2575-2710'. TOOH to 2071'. PT csg to 500 psi, OK. POOH w/85 jts 2 3/8" tbg. SDON.

6-8-95 TIH, ran 7" gauge ring to 2125'. TOOH. TIH, perf 4 sqz holes @ 2136'. Could not establish injection. (Verbal approval to change plans from Steve Mason, BLM). Perf 4 sqz holes @ 1984', could not establish injection. TOOH. Perf 4 sqz holes @ 1034'. Could not establish injection. (Verbal approval to change plans from Steve Mason, BLM). TIH to 2196'. Plug #3: pump 65 sx Class "B" cmt inside csg @ 1858-2196'. POOH to 1097'. Plug #4: pump 42 sx Class "B" cmt inside csg @ 879-1097'. TOOH. TIH, perf 2 sqz holes @ 225'. Establish circ down csg & out bradenhead w/5 bbl wtr. Plug #5: pump 91 sx Class "B" cmt down csg & out bradenhead. WOC. SDON.

6-9-95 ND BOP. Cut off WH. Pump 12 sx Class "B" cmt to fill 7" csg. Install dry hole marker w/45 sx Class "B" cmt. RD. Well plugged and abandoned 6-9-95.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Affairs Date 6/13/95

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

CONDITION OF APPROVAL, if any:

Date
APPROVED

JUN 21 1995

NMOCD