



(SUBMIT IN TRIPLICATE)
**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

Land Office
Lease No. 03385
Unit J. 10-6 Unit
1-0-01-930

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	Water Inc.	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 19, 1957

Well No. 18 is located 920 ft. from [N] line and 1020 ft. from [E] line of sec. 18
Sec. 18 30 R 6 W T. 10 N. R. 6 E.
(¼ Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Alamo Alamogordo New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6627 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

8-26-57 Total Depth 5620'. C. G. 1. L. 5770'.
 Water Fractured 1. L. perforated intervals: 5276-5280; 5304-5380; 5561-5576;
 5644-5674; 5721-5731; 5744-5754 with 100,000 gallons water and 100,000 sand.
 Breakdown pressure 2000, maximum pressure 3150, average treating pressure 1900.
 Injection rate 21.5 bbls./min. Flush 7,000 gallons. 1000 drops of 1 balls
 each 12 stages).



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company
 Address Box 577
Hamington, N.W. Mexico

Original Signed D. C. Johnston
 By _____
 Title Petroleum Engineer