



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 070001
Unit Northeast Blanco
Unit Agreement No. 1, Sec. 929

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

Subsequent Report of Sand-Water Draw

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

WORKOVERJune 25, 1958Well No. 3-10 is located 1650 ft. from NM line and 1650 ft. from W line of sec. 10

31/4 Section 10 30N 2W NM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco Masaverde Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6273 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

On 5/23/58, perforated the Point Lookout Zone thru 5 1/2" liner with 2 holes per foot 5380'-5470'. Sand-water fraced with 63,210 gallons of water (including flush) and 50,000 lbs. of sand. Maximum treating pressure 1300 PSI. Minimum treating pressure 425 PSI. Final pressure Zero PSI. Average injection rate 51.9 barrels per minute.

Set bridge plug at 5360' & perforated the Menefee & Cliffhouse Zones thru 5 1/2" liner with 2 holes per foot 5056'-5082', 5228'-5262' & 5328'-5348'. Sand-water fraced with 52,600 gallons of water (including flush) and 40,000 lbs of sand. Injected 50 rubber balls during treatment. Maximum treating pressure 1750 PSI. Minimum treating pressure 650 PSI. Final pressure Zero PSI. Average injection rate 40.3 barrels per minute.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company BLACKWELL & NICHOLS COMPANYAddress P.O. Box 1237Durango, Colorado

Original Signed
by DeLasso Loos
By DeLasso Loos

Title Field Superintendent