

## SUNDRY NOTICES AND REPORTS ON WELLS

1. oil well ☐ gas well ☒ other

Blackwood & Nichols Co., Ltd.

P. O. Box 1237, Durango, Colorado 81301

AT SURFACE: 1650' F/NL - 990' F/EL

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>
REPAIR WELL	<input checked="" type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>
(other)	

RECEIVED  
(NOTE: R  
cl  
FEB 25 1892  
U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6300' GL

Pull 2 3/8" tubing, set a drillable bridge plug in 4 1/2" casing at approximately 4900'; locate holes in 4 1/2" casing, repair by squeeze cementing. If no holes are located, we propose to perforate the 4 1/2" and 7" casing and circulate cement to surface between 7" and 10 3/4" casing. Drill 4 1/2" bridge, rerun 2 3/8" tubing and return well to production.

When well is abandoned the Pictured Cliffs, Fruitland, and Ojo Alamo formations will be adequately protected.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED DeLasso LOOS TITLE District Manager DATE February 24, 1982

APPROVED BY [Signature] TITLE \_\_\_\_\_  
 CONDITIONS OF APPROVAL IF ANY: 2 1002

For JAMES F. SIMS  
DISTRICT ENGINEER

~~See Instructions on Reverse Side~~

**NMOCC**