3-M.M.O.C.C. 1-Bill Cutler 1-Oliver Fowler 1-Wayne Smith 1-File

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Pool	Rlanco	···	Fo	Formation Mess Verde				County	Rio I	Arriba	
Init	ialX	•	_Annua			Spec	ial		_Date of	Test	8-12-57
Compa	any Pacifi	e Mort	hvest I	Pipelir	e Corp.	Lease_84	n Juan	31-6	Wel	1 No	12-2
Unit	y 7-5/8	Sec	qwT	301	Rge	. <u>6</u> w	Purc	haser 10	t commecte	d	
Casir	7-5/8 1g <u>5 } </u>	/t	I.	D	Set	353 at <u>59</u> 3	30 53 Pe	rf. 5286		То	5758
Tubir	ng 1-1/4 W	/t	I.	D	Set	at 57	30 Pe	erf	1	Го	
Gas Pay: From <u>5286</u> To <u>5758</u> L xG .650 -GL Bar.Press. 12											
Producing Thru: Casing Tubing Type Well single Single-Bradenhead-G. G. or G.O. Dual											
Date of Completion:PackerReservoir Temp											
							ED DATA				
Tested Through (Proces) (Choke) (Meter) Shut In 14 days Type Taps											
~			low Dat				Tubing		Casing Da		_
No.	(Prover) (Line)			Press.	j				Press.		Duration of Flow
	Size		- ,	psig	h _w	o _F .	psig	°F.	psig	[⊃] F•	Hr.
SI	·	3	/	216		62°	91.7 21.6	620	91.5 231		3
1. 2. 3.		3	/•	200		UE	210		46,34		
3.		1									
4. 5.		 	+					 			
FLOW CALCULATIONS Coefficient Pressure Flow Temp. Gravity Compress. Rate of Flow Factor Factor Q-MCFPD											
	(24-Hour) $\sqrt{h_{w}p_{f}}$			- F	sia		Ft F		Fpv		@ 15.025 psia
1.	14.1607				228	•9951		.9608	1.02		3164
1. 2. 3. 4.											
4.											
5.											
	quid Hydro y of Liqui		ocarbor			cf/bbl.	ALCUIATI	Speci	fic Gravit	ty Sepa	rator Gas_ ring Fluid 863.0
c	. 		\	<u>-e -7</u>				^г с	<u> </u>	_ ^r c	003.0
No.	P _w Pt (psia)	Pt2	Fc	ı	(F _c Q) ²	(F.	cQ) ² -e ^{-s})	243 P _w 2	$P_c^2 - P_w^2$	Ca P	y P _C
1.								59.0	804.0		1.07
3.											
1. 2. 3. 4.				$-\Gamma$							
	ute Potent	ial:	332	•		MCFPD;	n .7	5/ 1.052	0		
COMPANY Pacific Forthwest Pipeline Corporation											
ADDRESS 105 - West Broadway, Farmington, New Mexico AGENT and TITLE C. R. Wagner - Well Test Engineer											
agent Witne	SSED	E.R.	10000	<u> </u>	Well	. Test E	erkruser,		3		 -
COMPA										35	
	-					REM	ARKS	3	Co		

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure (P_W) . MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- P_w Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- P_{t} Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- $h_{\mbox{\scriptsize W}}^{-}$ Differential meter pressure, inches water.
- Fg Gravity correction factor.
- F_t Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_\pm .

AZTEC DISTRICT OFFICE

No. Copies Received 3

DISTRIBUTION

NO.
FURNISHED

Operator

Santa F4

Proretion Office

U. S. G. S.

Transporter

File