

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

SF-078997

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Northwest Pipeline Corporation

3. ADDRESS OF OPERATOR

3539 East 30th - Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface 990' FSL & 990 FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DE, RT, GR, etc.)

6315' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

1. TIH w/ 7" packer & tagged cmt @ 3676'. Set packer @ 3658' and pressure tested bottom cmt plug to 500 psi, held ok.
2. Perforated 3 holes @ 2570' (50' below bottom of Ojo Alamo) and 3 holes at 300' (50' below surface casing seat).
3. Spotted mud plug (Viscosity = 70 sec./qt., weight = 10.2 lbs/gal) from 3676' to 3430'.
4. Spotted cement plug from 3430' to 2860' (bottom of PC @ 3380', top of FRT @ 2918'). WOC 1.5 hrs. Tagged top of cement @ 2884'.
5. Spotted mud plug from 2884' to 2570'.
6. Squeezed Ojo Alamo with 66 sx Class "B" w/ 2% CaCl₂ from 2570' to 2275' & spotted a cement plug from 2570' to 2275' in 7" casing.
7. TIH & tagged top of cement @ 2274'.
8. Spotted mud plug from 2274' to 300'.
9. Circulated cement from 7"-10-3/4" annulus and spotted cement from 300' to surface inside 7" casing.
10. Cut off casinghead, installed P & A marker and cleaned up location.

18. I hereby certify that the foregoing is true and correct

SIGNED

Mark McCallister
Mark McCallister

TITLE

Engineer

DATE

7-17-89

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

Ken Townsend

*See Instructions on Reverse Side

ch-1

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

WELLCORE DIAGRAM

7/17/89

SAN JUAN 30-5 UNIT #3

Tops:

Ojo ALAMO	2325'
KIRTLAND	2520'
FRUITLAND	2718'
PICTURED CLIFFS	3259'
LEWIS	3380'

