

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or to backfill a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. SP 079000
2. NAME OF OPERATOR El Paso Natural Gas Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR Box 990, Farmington, New Mexico 87401		7. UNIT AGREEMENT NAME San Juan 31-6 Unit
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1660'S, 990'W		8. FARM OR LEASE NAME San Juan 31-6 Unit
14. PERMIT NO.		9. WELL NO. 6 (OVWC)
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 5558' G.L.		10. FIELD AND POOL, OR WILDCAT Blanco M. V.
		11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA Sec. 1, T-30-N, R-7-W N.M.P.M.
		12. COUNTY OR PARISH Rio Arriba
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☒	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☒	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☒
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) Squeeze	
(Other) ☐		(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

On 6-13-70 pulled tubing, set cement retainer at 5133' and tested casing to 1090# O. K. Squeezed open hole w/150 sacks of cement. Perforated 2 squeeze holes at 2602'. Set cement retainer at 2543', squeezed through peffs. w/125 sacks of cement.

On 6-17-70 T.D. 6048'. Ran 186 joints 4 1/2", 10.5#, K-55 csg. (6037') set at 6048' w/125 sacks of cement. W.O.C. 18 hours.

On 6-18-70 P.B.T.D. 6036'. Perf. 5730-38', 5754-70', 5792-5808', 5846-54', 5874-82', 5930-38', 5950-98' w/16 SPZ. Frac w/80,000# 20/40 sand, 63,862 gal. water. Dropped 6 sets of 16 balls, flushed w/4998 gal. water. Pumped bridging ~~and~~ ball to baffle at ~~4000~~ 5640', tested C. K. Perf. 5390-98', 5434-42', 5496-5506', 5580-88' w/16 SPZ. Frac w/50,000# 20/40 sand, 50,064 gal. water, dropped 3 sets of 16 balls, flushed w/3738 gal. water.

RECEIVED

JUN 29 1970

U.S. GEOLOGICAL SURVEY

18. I hereby certify that the foregoing is true and correct

SIGNED W. J. WOOD

TITLE Petroleum Engineer

DURANGO, COLO

DATE 6-26-70

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not stated off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963 O-685229

847-485

