


(SUBMIT IN TRIPLICATE)

Land Office Santa Fe

Lease No. 079001

Unit Northeast Blanco

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY Unit Agreement No. 1, Sec. 929



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REPAIR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 26, 1962

Well No. 16-3 is located 990 ft. from N line and 990 ft. from E line of sec. 3

NE/4 Section 3 30N 7W RMPM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco Mesaverde Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6277 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Pull 2-3/8" tubing and set drillable bridge plug in the 7" casing. Locate and squeeze cement any holes found in 7" casing. Drill plug, clean out to TD, run 4 1/2" or 5" casing and circulate cement to surface. Perforate and sand-water fracture the Mesaverde Zone, rerun tubing and return well to production.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Blackwood & Nichols Company (Unit Operator)
Address P. O. Box 1237
Durango, Colorado
By Delasso Loos
Title Field Superintendent