Form 9-831 a (Feb. 1961)



## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

iget Bureau No. 42-R358.4. orm Approved.

Santa Fe Land Office

079074

San Juan 30-6 Unit

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO PULL OF ALTER CASING NOTICE OF INTENTION TO ABANDON WEL! Notice of Intention to Workover Well	SUPPLEMENTARY WELL HISTORY	U.S. GEOL	r	
NOTICE OF INTENTION TO SHOUT OF A HEIZE	SUBSECUENT REPORT OF ABANDONMENT	DE0		1002
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSECUENT REPORT OF RE-DRILLING OR REPAIR	DEC	6	1962
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	Ш		
NOTICE OF INTENTION TO CHANGE PLAN	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	REG		VS
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	DEP	le n	WF

INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA

December 6 1962 is located 990 ft. from  $\frac{x + x + x}{|S|}$  line and 990 ft. from  $\frac{x + x + x}{|W|}$  line of sec. Well No. 27 SW/4 Sec. 27 30N Blanco Mesa Verde Rio Arriba The elevation of the derrick floor above sea level is 6909 ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of propo-ing points, and all other important proposed work)

It is intended to re-work this well in the following manner:

- If tubing can be pulled:
  - 1. Pull tubing and clean out to 6130'.
  - 2. Run a full string of 2 7/8" casing and cement.
  - 3. Perforate and fracture Mesa Verde formation, clean out and run tubing.
- B. If tubing cannot be pulled:
  - 1. Cut tubing below 5 1/2" casing shoe.
  - 2. Set 5 1/2" retainer at approximately 5390' and squeeze open hole.
  - 3. Set whipstock and drill to 6130'.
  - 4. Complete as above.

l understa	nd that this plan of work must receive approval in	writing by the Geological Survey before operations may be commenced.
Company		
Address	Box 990	
	Farmington, New Mexico	By Muly
		Title Petroleum Engineer