

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office **New Mexico**

Lease No. **02151**

Unit

**RECEIVED**

**JUL 3 1962**

**SUNDRY NOTICES AND REPORTS ON WELLS**

U. S. GEOLOGICAL SURVEY  
FARMINGTON, NEW MEXICO

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	
Notice of Intention to Workover <b>XX</b>	

INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA:

June 29, 1962

Whitley  
Well No. **4-B** is located **940** ft. from **XXX** line and **1750** ft. from **XXX** line of sec. **28**  
**SW/4 Section 28** **30-N** **7-W** **N.M.P.M.**  
**Blanco Mesa Verde** **Rio Arriba** **New Mexico**

The elevation of the derrick floor above sea level is **6280** ft.

**DETAILS OF WORK**

State names of and expected depths of objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work.

It is intended to re-work this well in the following manner:

- A. If tubing can be pulled:
1. Pull tubing. Mud up and Clean out to 5500', (casing will be set to open hole depth if hole is open below 5520'.)
  2. Run 2 7/8" long string & cement from T.D. to 4583'.
  3. Run G/R Neutron, perforate & fracture.
  4. Clean out & run tubing.
- B. If tubing cannot be pulled:
1. Run free point and cut tubing (at least 50' below base of 5 1/2" casing).
  2. 5 1/2" retainer near bottom of 5 1/2" casing & squeeze open hole.
  3. Pressure up on retainer. If casing leaks, mud drill. If csg. does not leak, gas drill
  4. Set whipstock & drill to 5520'.
  5. Run G/R after pipe, if gas drilled. Run I-ES before pipe if mud drilled. Run 2 7/8" long string & cement, bringing cement 100' into intermediate casing.
  6. Complete as above.

Company **El Paso Natural Gas Company**

Address **Box 990**

**Farmington, New Mexico**

By

*A. W. Mehan*

Title **Petroleum Engineer**