

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

STANDARD FORM NO. 10
MAY 1962 EDITION
GSA GEN. REG. NO. 27

THIS FORM IS USED FOR
REPORTING ON THE RESULTS OF
WELL LOGGING AND SURVEYING

NM 012694

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for reporting on a well which is a different reservoir.
For a different reservoir, use Form 10-2, "Sundry Notices and Reports on Wells".)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME San Juan 30-6 Unit
2. NAME OF OPERATOR El Paso Natural Gas Company		8. FARM OR LEASE NAME San Juan 30-6 Unit
3. ADDRESS OF OPERATOR PO Box 990, Farmington, NM 87401		9. WELL NO. 83-Y
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1911'N, 1290'E		10. FIELD AND POOL, OR WILDCAT Blanco Mesa Verde
		11. SEC., T., R., M., OR BLK. AND SUEVLY OR AREA Sec. 15, T-30-N, R-7-W NMPM
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6220'GL	12. COUNTY OR PARISH Rio Arriba
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

Temporarily Abandonment ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

on 10-2-71: Spudded well, drilled surface.

on 10-3-71: Ran 6 joints, 9 5/8", 32.3#, H-40 surface casing, 198'-set at 212'.
cemented with 190 sks. circulated to surface. WOC 12 hours, held
600 psi for 30 minutes.

on 10-8-71: While drilling at 3125' well blew out from the Fruitland.

from 10-8-71 to 10-14-71: Attempted to control well with weighted mud unsuccessfully.

on 10-14-71: Ran drill pipe to 2900' and cemented with 1635 sacks cement, circulated.
Displaced cement from drill pipe with fresh water. Top good cement at 75'
by temperature survey. Cleaned and leveled location.

Well is now temporarily abandoned. Will cement inside drill pipe, set Plug and Abandoned
marker and file plug and abandonment report at a later date.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Petroleum Engineer

DATE January 6, 1972

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

DATE

RECEIVED

*See Instructions on Reverse Side

JAN 7 1972

U. S. GEOLOGICAL SURVEY