

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other in-
structions on
reverse side)FOR APPROVED
OMB NO. 1004-0137
Expires December 31, 1991

5. LEASE DESIGNATION AND SERIAL NO.

SF-079383

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 30-6 Unit

8. FARM OR LEASE NAME, WELL NO.

San Juan 30-6 U #95R

9. API WELL NO.

30-039-20520

10. FIELD AND POOL, OR WILDCAT

La Jara Pict. Cliffs

Blanco Mesaverde

11. SEC., T., R., M., OR BLOCK AND SURVEY
OR AREA

Sec. 26, T-30-N, R-7-W

12. COUNTY OR
PARISH

Rio Arriba

13. STATE

NM

1a. TYPE OF WELL:

OIL WELL ☐GAS WELL ☒DRY ☐Other ☐

b. TYPE OF COMPLETION:

NEW WELL ☐WORK OVER ☐DEEP-EN ☐PLUG BACK ☐DIFF. REMV. ☒Other ☐

2. NAME OF OPERATOR

Burlington Resources Oil & Gas Company

3. ADDRESS AND TELEPHONE NO.

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface

800' FSL, 875' FWL

At top prod. interval reported below

At total depth

14. PERMIT NO.

DATE ISSUED

15. DATE SPUDDED

8-30-72

16. DATE T.D. REACHED

9-9-72

17. DATE COMPL. (Ready to prod.)

11-24-96

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

6864 GR

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

6317

21. PLUG, BACK T.D., MD & TVD

3867

22. IF MULTIPLE COMPL.,

23. INTERVALS

DRILLED BY

ROTARY TOOLS

CABLE TOOLS

0-6317

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (RD AND TOWN)

3747-3854 Pictured Cliffs

26. TYPE ELECTRIC AND OTHER LOGS RUN

CNL-CBL-CCL-GR

27. WAS WELL CORRED

No

28.

CASING RECORD (Type of strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
9 5/8	32.3#	222	13 3/4	224 cu.ft.	
7	20#	4104	8 3/4	290 cu.ft.	

29.

LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
4 1/2	3935	6317	408 cu.ft.		2 3/8	3839	3025

31. PERFORATION RECORD (Interval, size and number)

3747, 3749, 3753, 3759, 3754, 3773,
3775, 3780, 3787, 3795, 3799, 3802,
3810, 3818, 3823, 3827, 3841, 3845,
3854

See back for squeezes

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
3747-3854	104,484# 20/40 Brady sd
	16,363 gal 20# linear gel
	513,000 SCF N2

33.*

PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
11-24-96		Flowing				SI	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
11-24-96			→		707 Pitdt Gauge		
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	
SI 995	SI 0	→					

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

None

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

TITLE Regulatory Administrator

DEC 30 1996

DATE 12-23-96

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOC

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	38. GEOLOGIC MARKERS		
				NAME	TOP MEAS. DEPTH	TRUE VERT. DEPTH
			Pump 120 sx Class "B" cmt below cmt retainer @ 5508' Pump 1 bbl cmt on top of cmt retainer Pump 25 sx Class "B" cmt @ 2773-2901' Pump 130 sx Class "B" cmt below pkr @ 1620' Pump 25 sx Micro Matrix cmt @ 2387-2610' Pump 24 sx Class "B" cmt @ 2673-2894'	Mesaverde Point Lookout PC	5537 5919 3746	