

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved
Budget Bureau No. 42-R1424
LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

Use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use APPLICATION FOR PERMIT for such proposals.

NM - 4457
B. IF INDIAN, ALLOTTEE OR TRIBE NAME

C. UNIT AGREEMENT NAME

D. FARM OR LEASE NAME

SCHALK 57

9. WELL NO.

2

10. FIELD AND POOL, OR WELL CAT

BLANCO MESA VERDE

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

SEC. 12, T-30N, R-5W

12. COUNTY OR PARISH 13. STATE

RIO ARriba NEW MEXICO

935' FROM THE NORTH LINE, 985' FROM THE EAST LINE

14. TERM OF NO.

15. ELEVATIONS (Show whether OF, AT OR, ETC.)

6575' GR

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

SOURCE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PUT IN OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

ALTER TREAT

MULTIPLE COMPLETION

FRACTURE TREATMENT

ALTERING CASING

STOP WORK - LEASE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

WELL HISTORY

X

16. (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
17. (Note: If used for completed operations, clearly state in pertinent details, and give pertinent dates, including estimated date of starting any new work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

SCHALK 57 WELL NO. 2

SPUDDED: 10-01-74

TOTAL DEPTH: 6100' ON 10-19-74

10-20-74

RAN 1/4 JOINTS OF 4-1/2" O.D. 10.50# TOTALING 6114' SET AT 6100 RKB. (53 JOINTS WERE K-55.) D.V. TOOLS SET AT 2005' AND 4001'. FLOAT SET AT 6059'. CEMENTED FIRST STAGE WITH 220 SACKS HALLIBURTON LIGHTWEIGHT WITH 12-1/2# GELSONITE PER SACK AND 160 SACKS 40/50 POSMIX WITH 12-1/2# GELSONITE PER SACK. CEMENTED 2ND STAGE WITH 286 SACKS HALLIBURTON LIGHTWEIGHT WITH 12# GEL WITH 1/4# FLOSEAL PER SACK. PLUG DOWN AT 10:30 AM. CEMENTED 3RD STAGE WITH 350 SACKS HALLIBURTON LIGHTWEIGHT WITH 12# GEL, 12-1/2 GELSONITE AND 1/4# FLOSEAL PER SACK. HAD GOOD CIRCULATION. PLUG DOWN AT 1:30 PM.

PERFORATIONS

5664' TO 5700'
5740' TO 5758'

5774' TO 5810'
5898' TO 6010'

1 SHOT/FOOT

SIGNATURE: *John E. Schalk*
TITLE: AGENT

AGENT

DATE: 10-28-74

APPROVED BY:
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side