

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN THIS MANNER  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. Jicarilla 511 30-039-21036	
2. NAME OF OPERATOR Union Oil Company of California		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Jicarilla	
3. ADDRESS OF OPERATOR P. O. Box 2620 - Casper, Wyoming 82601		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 577' FSL & 2303' FWL		8. FARM OR LEASE NAME Jicarilla	
14. PERMIT NO.		9. WELL NO. 1-N31	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 7442' G.L.		10. FIELD AND POOL, OR WILDCAT Wildcat	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 31, T.30N., R.1W.	
		12. COUNTY OR PARISH Rio Arriba	
		13. STATE New Mexico	

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:


WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐Supplementary Well History ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

## 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 12-1/4" hole at 2:15 p.m. 12-23-74

Drilled to 453'. Ran 17-1/2" hole opener and opened 12-1/4" hole to 17-1/2" from surface to 453'. P.O.O.H.

Ran and cemented 9 joints and 1 piece (387.95') of 13-3/8", H-40, 48#, 8RD, ST&C, new casing at 400' with 500 sacks regular cement with 2% CaCl<sub>2</sub> mixed at 15.5#/gal. Cement circulated to surface, approx. 50 sacks to pit. C.I.P. and J.C. at 12:30 p.m. 12-25-74. Bumped plug and released pressure. Float held O.K. W.O.C.

(Verbal approval for Permit to Drill received from U.S.G.S. on 12-23-74.)

## 18. I hereby certify that the foregoing is true and correct

SIGNED

  
R. G. Ladd, Jr.

TITLE District Drilling Supt.

DATE 12-26-74

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: