UNITED STATES SUBMIT IN TRIPLICATE DEPARTMENT OF THE INTERIOR (Other Instructions on reverse side)

Form approved. Budget Bureau No. 42 R1424.

5 .	LEASE DESIGNATION AND				SEKIAL	NO.
	c					

SECLOGICAL SURVEY	1 DI 000000 7
TOTAL AND DEDODITE ON MELLO	6. IF INDIAN, ALLOTTEE OR TRIBE NA

					6. IF INDIAN, ALLO	TTEE OR TRIBE NAME		
(Do not use this fo	rm for propos	ICES AND REP als to drill or to deep TION FOR PERMIT—	en or plug b	ack to a different reservoir.				
1.					7. UNIT AGREEMENT	' NAME		
OIL GAS WELL	OTHER				<u> </u>	San Juan 30-5 Unit		
2. NAME OF OPERATOR	A OTHER				8. FARM OR LEASE			
Northwest	Pinolina	Corporation		16 m	San Jua	an 30-5 Unit		
3. ADDRESS OF OPERATOR	Therine	Corporation		1 6 3	9 WELL NO.	111 30-3 01:11		
P O Roy	00 Fart	mington New M	favi co	87401 State requirements. OF	S- 44			
4. LOCATION OF WELL (Re)	ort location c	learly and in accordance	ce with any	State requirements.	10. FIELD AND POOL	OR WILDCAT		
See also space 17 below At surface	.)				Blanco	Mesa Verde		
1850	FSL &	1165' FWL			11. SEC., T., R., M.,			
					SURVEY OR A	REA		
					Sec. 6.	, T30N, R5W		
14. PERMIT NO.		15. ELEVATIONS (Show	w whether DF.	RT, GR, etc.)	12. COUNTY OR PAR	<u> </u>		
		6394' (•	Rio Arriba	N.M.		
	<u> </u>	<u> </u>						
16.	Check Ap	propriate Box To I	ndicate N	lature of Notice, Report, o	r Other Data			
No	TICE OF INTEN	TION TO:		SUBS	SEQUENT REPORT OF:			
TEST WATER SHUT-OFF		PULL OR ALTER CASING		WATER SHUT-OFF	REPAIRIN	IG WELL		
FRACTURE TREAT		MULTIPLE COMPLETE		FRACTURE TREATMENT	X ALTERIN	G CASING		
SHOOT OR ACIDIZE		ABANDON*		SHOOTING OR ACIDIZING	ABANDON	MENT*		
REPAIR WELL		CHANGE PLANS		(Other)	"Completion"			
(Other)				(Note: Report rest	ults of multiple completi empletion Report and Log	on on Well		
9-19-75 Drilled 8 3/4" hole to 3721' KB with mud. Ran 92 joints (3709') 7", 20#, K-55 casing set @ 3721' KB. Cemented w/160 sks. cement. WOC 12 hours. 9-20-75 Top of cement @ 2000' by temp. survey. 9-23-75 Drilled 6 1/4" hole to 5906' with gas. Ran Gamma Induction and Gamma Density logs. Ran 56 joints (2354') 4 1/2", 10.5#, K-55 casing liner Top @ 3552', F.C. @ 5862', shoe @ 5905' KB. Cemented w/215 sks. WOC 18 hours.								
9-24-75	Tested liner to 1500 PSI-OK. Spotted 500 gal. 7 1/2% HCl and perforated from 5320' to 5820' w/19 shots.							
9-25-75	Frac'd v	7/70-000 # 20	/40 sand	d and 80,000 gal. t	reated water			
9-28-75	tubing, set @	5700 ND						
7 20 73	tubing, set e	2/90 KD.						
	RICKEU	werr orr furd	Lubing.	. Shut-in well.				
					607 8 1073			
18. I hereby certify that the	ne foregoing is	true and correct	***************************************	· ·		V. 1		
SIGNED 7/	Marin	relli r	ITLE P	etroleum Engineer	DATE OC	tober 2, 1975		
(This space for Federa	Maronce l or State offi							
APPROVED BY		m	imi ir		To 4 20070			

CONDITIONS OF APPROVAL, IF ANY: