

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 079060

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Northeast Blanco Unit  
Agrmt. No. 1, Sec. 929

8. FARM OR LEASE NAME

Northeast Blanco Unit

9. WELL NO.

4A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesaverde

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

D-21-30N-7W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6264' GL

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other)

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

8-4-78 Perforated first stage, 4 holes/ft/interval; 5408' 5482' 5492' 5502' 5542' 5556' 5624' 5642' and 5678'; 36 holes. Sand-water fractured with 95,080 gallons water with 2# FR-20/1000 gallons water and 80,000 lbs of 20-40 sand. Maximum treating pressure 1900 PSI, average treating pressure 1400 PSI, average injection rate 60 bbls/min.

8-5-78 Set bridge plug at 5340'. Perforated second stage four holes/foot/interval; 5018', 5024', 5032', 5040', 5050', 5106', 5142', 5222' and 5252'; thirty-six holes. Sand-water fractured with 84,110 gallons water with 2# FR-20 per 1000 gallons water and 70,000 lbs of 20-40 sand. Maximum treating pressure 1600 PSI, average treating pressure 1600 PSI, average injection rate 68 bbls/min.

18. I hereby certify that the foregoing is true and correct

SIGNED

DeLasso Loos

TITLE

District Manager

DATE

8-8-78

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:



RECEIVED

AUG 9 1978

\*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY  
DURANGO, COLO.