

Form 9-331
Dec. 1973Form Approved.
Budget Bureau No. 42-R1424UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well2. NAME OF OPERATOR
EL PASO NATURAL GAS CO.3. ADDRESS OF OPERATOR
BOX 990, FARMINGTON, NEW MEXICO4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 640' N, 800' W
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐☒
☒
☐
☐
☐
☐
☐
☐

5. LEASE

NM 012709

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 30-6 Unit

8. FARM OR LEASE NAME

San Juan 30-6 Unit

9. WELL NO.

8A

10. FIELD OR WILDCAT NAME

Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 31, T-30-N, R-7-W
NMPM

12. COUNTY OR PARISH

13. STATE

Rio Arriba

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6050' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7/21/78: T.D. 3251'. Ran 80 joints 7", 20#, K-55 intermediate casing, 3240' set at 3251'. Cemented with 319 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 750'.

7/26/78: T.D. 3857'. Ran 107 joints 4 1/2", 10.5#, KS production casing, 3846' set at 3857'. Float collar set at 3169'. Cemented with 85 cu. ft. cement. WOC 18 hours.

7/27/78: PBTD 3849'. Tested casing to 2500#, OK. Perfed 3829-3849' w/2 SPF. Natural Completion.

Subsurface Safety Valve: Manu. and Type _____

Set @ _____ FL.

18. I hereby certify that the foregoing is true and correct

SIGNED N. P. Luces TITLE Drilling ClerkDATE 7-31-78

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY: