Form 9-331 (May 1963)	DEPAR	UNITED STATE RTMENT OF THE GEOLOGICAL S	E INTERIO	SUBMIT IN TR (Other instructi verse side)	IPLICATE*	5. LEASE DESIGNATIO	reau No. 42-R142 N AND SERIAL NO
(De	SUNDRY NO not use this form for pruse "APPI	OTICES AND RE	PORTS ON	WELLS to a different reser	voir.	SF 079001.	
OIL GAS WELL XX OTHER 2. NAME OF OPERATOR						7. UNIT AGREEMENT NAME Northeast Blanco Unit Agrmt. No. 1, Sec. 929 8. FARM OR LEASE NAME	
Blackwood & Nichols Co., Ltd. 3. ADDRESS OF OPERATOR						Northeast Blanco Unit	
P. O. Box 1237, Durango, Colorado 81301 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* At surface						102A 10. FIELD AND POOL, OR WILDCAT Blanco Mesaverde	
1810' F/NL - 1540' F/WL						11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA F-3-30N-7W	
14. PERMIT	NO.	15. ELEVATIONS (Sho	w whether DF, RT,	GR, etc.)		12. COUNTY OR PARISI	H 13. STATE
16.	Check A			(N) :: D		Rio Arriba	New Mexic
	NOTICE OF INT	Appropriate Box To	ınaicais Main	re of Notice, Kep		ther Data	
FRACTU SHOOT (REPAIR (Other) 17. DESCRIBE propos nent to 9-8-78	rrorosed on completed of ed work if well is directly this work). Spudded 12 1/4 circulation. with 150 sacks Cement circula	" hole at 6:00 Ran 5 jts 9 5/8 of Class B cen ted.	P.M., 9-7 B" 36.00# pent with	(Note: Rep. Completion of Comp	DIZING DIZING DIZ NG Ce Ort results co ort Recomple ent dates, i rue vertical irculat 208' so lug down	REPAIRING ALTERING C ABANDONME Ment Becord of multiple completion tion Report and Log for ncluding estimated dat depths for all markers ion at 125'; net at 224'; ce n 8:00 P.M., 9	on Well rm.) te of starting any s and zones perting and semented 9-8-78.
91378	Ran Induction Electric, Compensated Density and Sidewall Neutron. Ran 88 jts 7" 23.00# K-55 casing, 3564' set at 3579'. Cemented with 200 sacks of Howco Lite with 1/4# flocele per sack, followed with 100 sacks of Class B with 2% CaCl and 1/4# flocele per sack. Plug down 10:00 A.M., 9-13-78. Ran temperature survey, top cement at 1725'. Tested 7" casing to 1000 PSI for 30 minutes, held OK.						
9-15-78	Ran Induction E jts 4 1/2" 10.5 Brown PBR tool 50-50 poz-mix w gilsonite per s cement.	at 3401', floadith 2% gel and	; 2331° se t collar a .0 6% FIA	t at 5938'. t 5897'. Ce	Top of mented	liner at 339 with 300 sack	0'; s of

*See Instructions on Reverse Side

TITLE .

(This space for Federal or State office use)

APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

U. S. GEOLOGICAL SURVEY DURANGO, COLO.

SEP 1 9 1978

DATE

DATE